

SHR-24C-6.35-9.525 Cut Sheet



Sung-II Machinery drive coupling, servo high gain, aluminum alloy, clamp, size 24, 1/4 x 3/8in bore.

For complete product information, please see this item on our store at the following link:



<https://www.automationdirect.com/pn/SHR-24C-6.35-9.525>

Technical Specifications

Brand	Sung-II Machinery
Item	Drive coupling
Coupling Type	Servo high gain
Material	Aluminum alloy
Rated Torque	3.5 N·m
Maximum Torque	7 N·m
Slip Torque	3.3 N·m
Maximum Angular Misalignment	1.5 degrees
Maximum Parallel Misalignment	0.15mm

Maximum RPM	25000
Attachment Style	Clamp
Coupling Size	24
Overall Length	31.2mm
Bore Diameter	1/4in
Bore Diameter 2	3/8in
Outside Diameter	23.8mm
Clamp Screw Fastening Torque	1.1 N·m
Clamp Screw Size	M2.6-0.45 x 8mm

Agency Approvals

UL Listed File #	None
UL Recognized File #	None
UL Hazardous File #	None
CE	None
CSA File #	None
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	View EU REACH document
Other	RoHS Statement

Dimensional Drawings



2D Drawing PDF Link:
<https://cdn.automationdirect.com/static/drawings/2d/SHR-24C-6.35-9.525.pdf>
See store item page for other formats.