SR55-242 Cut Sheet





Stellar SR55 series full-featured soft starter, 242A, 200-480 VAC at 3-phase, Trip Class 10/20/30, rated for 3 start/hour, internally bypassed, 3 frame. Optional EtherNet/IP and Modbus TCP cards available.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/SR55-242

Technical Specifications

Brand	Stellar
Item	Soft starter
Controller Type	Full-featured
Series	SR55
Amperage Rating	242A
Nominal Input Voltage	208 VAC/220-240 VAC/440-480 VAC
Nominal Output Voltage	208 VAC/220-240 VAC/440-480 VAC
Trip Class	Trip Class 10/20/30
Starts per Hour	3
Internally Bypassed	Yes
Number of Input Phases	3
Number of Output Phases	3
Number of Controlled Output Phases	3
Control Mode	Sinusoidal
Control Power Requirement	24 VDC and 110 VAC or 230 VAC
Communication Port and Connection Type(s)	(1) RS-485 (RJ12)
Port Protocol(s)	Modbus RTU
Port Speed(s)	up to 115.2k baud

Derating	Unit may require derating for applications
	other than fans and pumps; see
	specifications for appropriate derating
Temperature Rating	-20 to 50 deg C
Enclosure Type	Open
Mounting	Panel
Frame Size	3
IP Rating	IP00
Output Frequency Range	0-60 Hz
Output Type	SCR output
Reverse Capability	None
SCCR Rating	18kA SCCR
Additional Information	Optional EtherNet/IP and
	Modbus TCP cards available
Dangerous Goods	Battery Installed: Yes
	Packaging Instructions: 970
	UN Number: UN3091
	Hazard Type: Lithium Batteries
	Battery Type: Button
	Lithium Content: 0.04
	Replacement Battery: BR1632
	Generic Battery: BR1632

Agency Approvals

UL Listed File #	ETL
UL Recognized File #	None
UL Hazardous File #	None
CE	View CE declarations
CSA File #	ETL
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document
Other	Link to ETL Website

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/SR55-242.pdf See store item page for other formats.