TLE Cut Sheet





Laumas analog load cell transmitter, (4) load cell input(s), +/-39 mV, analog output, Modbus RTU, 12-24 VDC operating voltage. For use with 4- or 6-wire load cells. Up to (8) load cells can be connected.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/TLE

Technical Specifications

•	
Brand	Laumas
Item	Load cell transmitter
I/O Module Type	Analog
Number of Load Cell Inputs	4
Input Load Cell Signal Range	+/- 39 mV
Input Resolution	24-bit
Input Excitation Voltage	5 VDC
Number of Analog Output Channels	1
Analog Output Signal Type	Current/voltage
Number of Non-Isolated Analog Output Commons	1
Output Resolution	16-bit

Output Current Signal Range	0-20 mA and 4-20 mA
Output Voltage Signal Range	0-5 VDC, 0-10 VDC, +/- 5 VDC and +/- 10 VDC
Communication Port and Connection Type(s)	(1) RS-485 (2-pin terminal)
Port Protocol(s)	Modbus RTU Slave
Port Speed(s)	up to 115.2k baud
Mounting	35mm DIN rail
Operating Voltage	12-24 VDC
Display Type	Two-line, 8-digit, LCD
For Use With	4- or 6-wire load cells
Additional Information	Up to (8) load cells can be connected

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/2d/TLE.pdf See store item page for other formats.

Agency Approvals

UL Listed File #	None
UL Recognized File #	E365453
UL Hazardous File #	None
CE	View CE declarations
CSA File #	None
RoHS Status	Yes (See CE Doc)
EU REACH	View EU REACH document