<u>V40176-1</u> Cut Sheet





Southwire flexible control cable, unshielded, 12 conductors (includes ground), 18 AWG, bare copper, PVC/Nylon conductor insulation material, black with white numbers and green/yellow ground, TPE jacket, gray, cut to length.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/V40176-1

Technical Specifications

Brand	Southwire
Item	Cable
Wire/Cable Type	Control
UL Wire/Cable Type	TC, TC-ER, WTTC and MTW
Application	General purpose
Flexibility	Flexible
Voltage Rating	600V (Types TC, TC-ER, MTW), 1000V (Type WTTC)
Conductors	12 conductors (includes ground)
Conductor Size	18 AWG
Conductor Stranding	16-stranded
Conductor Material	Bare copper
Conductor Insulation Material	PVC/Nylon

Conductor Insulation Color	Black with white numbers and green/yellow ground
Shielding	Unshielded
Jacket Material	TPE
Jacket Color	Gray
Nominal Overall Cable Diameter	0.44in
Bulk Length	Cut to length
Package Type	 1 to 50ft = Coil 51 to 200ft = 14 x 7in Reel 201 to 280ft = 14 x 10in Reel 281 to 440ft = 16 x 10in Reel 441 to 630ft = 18 x 10in Reel 631 to 810ft = 18 x 13in Reel 811 to 1750ft = 24 x 17in Wooden Reel 1751 to 2890ft = 30 x 17in Wooden Reel 2891 to MAX = Large Wooden Reel

Agency Approvals

UL Listed File #	E75755
UL Recognized File #	None
UL Hazardous File #	None
CE	None
CSA File #	90458
RoHS Status	Meets RoHS Chemical Restrictions - No CE (See RoHS Statement Below)
EU REACH	Vew EU REACH document
Other	RoHS Statement