Y366 Cut Sheet





Marathon MicroMAX high efficiency AC induction motor, highperformance inverter duty, 1-1/2hp, 3-phase, 230/460 VAC, 1800rpm, TENV, NEMA 145TC frame, rolled steel, C-face/ removable rigid base mount.

For complete product information, please see this item on our store at the following link:



https://www.automationdirect.com/pn/Y366

Technical Specifications

| Brand | Marathon |
|-------------------|--------------------------------|
| Item | Motor |
| Series | MicroMAX |
| Efficiency Group | High efficiency |
| Efficiency | 85.5 |
| Voltage Type | AC |
| Motor Type | Induction |
| Motor Application | High-performance inverter duty |
| Horsepower Rating | 1-1/2hp |
| Number of Phases | 3 |
| Voltage Rating | 230/460 VAC |
| Synchronous Speed | 1800rpm |
| Nameplate RPM | 1755rpm |
| Overload Type | None |
| Enclosure Type | TENV |
| Shaft Type | Round with square key |

| Shaft Diameter | 7/8in |
|--------------------------|--------------------------------|
| Shaft Material | 1144 Stressproof (C-223) steel |
| Motor Frame | NEMA 145TC |
| Frame Material | Rolled steel |
| Electrically Reversible | Yes |
| Insulation Class | Class H |
| IP Rating | IP43 |
| Constant Torque Rating | 1000:1 |
| Variable Torque Rating | 10:1 |
| Service Factor | 1.0 |
| Integrated Brake | No |
| NEMA Design | Design A |
| Junction Box Orientation | F3 |
| Mounting | C-face/removable rigid base |
| Mounting Orientation | Horizontal |
| Manufacturer Part Number | 145THTR5329 |

Dimensional Drawings



2D Drawing PDF Link: https://cdn.automationdirect.com /static/drawings/Y366.pdf See store item page for other formats.

Agency Approvals

| UL Listed File # | None |
|----------------------|------------------------|
| UL Recognized File # | E49747 |
| UL Hazardous File # | None |
| CE | View CE declarations |
| CSA File # | LR37479 |
| RoHS Status | No |
| EU REACH | View EU REACH document |