

## Premium efficiency motors for energy conservation

IronHorse® Premium Efficiency AC electric motors meet the requirements of the Energy Independence and Security Act of 2007. The MTCP2 Series gives you a low cost of entry so you get a quicker payback on your investment. All our Ironhorse motors are in stock and ready for same-day shipment; if your order is over \$49, you get free shipping too!

# Cast Iron T Frame Motors 1 to 300 hp TC Frame up to 30 hp

Premium efficiency, *c*CSA<sub>US</sub> certified, ISO9001, CE Mark, Standards of Excellence

All cast iron frame ribbed design for maximum cooling



**IRONHORSE®**  
AUTOMATIONDIRECT®

Class F winding insulation

starting at  
**\$226.00**

NSK/SKF/NTN brand premium quality ball (1-75 hp) or roller (100-300 hp) bearings

Standard NEMA T frame up to 300 hp (C-flange kit optional) TC frame models (C-face) available up to 30 hp

All MTCP2 models are totally enclosed fan cooled (TEFC)

Steel fan cover

Cast iron junction box with rubber gasket and rubber dust curtain

Solid (full frame length) cast iron mounting feet



## Three-phase - 208-230/460 Volt, T Frame - TEFC Enclosure, 1200,1800, 3600 RPM

- Premium Efficiency
- Premium grade quality
- All cast iron frames
- Drive-end ball bearings (1-75 hp) or roller bearings (100-300 hp) are installed in all MTCP2 motors
- Electrically reversible
- C-flange kits for C-face mounting are available
- C-face models available up to 30 hp



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

**T-Frame TEFC Motors – 3-phase Industrial Duty – 1 to 300 hp**

**TC-Frame (C-Face) TEFC Motors – 3-phase Industrial Duty – 1 to 30 hp**



**Premium Efficiency  
3-phase Cast-iron T-Frame**

## Features

- Available in 1200, 1800, & 3600 rpm
- Totally Enclosed Fan Cooled (TEFC) enclosure
- NEMA TC-frame (C-face) and T-frame motors
- Horizontal or Vertical shaft down orientation
- Cast-iron frame with ribbed design for maximum cooling
- Solid full frame length cast-iron mounting feet
- Steel fan cover
- Cast-iron junction box with rubber gasket and rubber dust cover
- NSK/NTN/SKF brand premium quality ball (1-75 hp) or roller bearings (100-300 hp)
- Maintenance free bearings (10 hp and below)
- V-ring shaft seals on drive end and on opposite drive end
- Electrically reversible
- Class F winding insulation
- Service Factor: 1.25 (1-200 hp), 1.15 (250-300 hp), 1.0 with AC drive (ALL)
- Meets or exceeds Premium Efficiency standards
- Class I, Div 2 hazardous locations
- Inverter ratings: 20:1 (variable torque); 10:1 (constant torque)
- Two year warranty
- cCSA<sub>us</sub> certified, ISO9001, CE

## Accessories & Spare Parts Available

- STABLE motor slide bases for adjustable mounting
- C-flange kits (for converting T-frame motors to TC-frame)
- Replacement junction boxes
- Replacement fans
- Replacement fan shrouds

## Applications

- Fans
- Conveyors
- Pumps
- Material Handling
- Metal Processing
- Textile Processing
- Test Stands



**Premium Efficiency  
3-phase Cast-iron TC-Frame**



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

T-Frame TEFC Motors – 3-Phase Industrial Duty – 1–300 hp – 1800 rpm

TC-Frame (C-Face) TEFC Motors – 3-Phase Industrial Duty – 1–30 hp – 1800 rpm

Motor Specifications – Premium-Efficiency MTCP2 Series 3-phase Motors – 1800 rpm													
Part Number (1)	Price	HP (2)	Base RPM @60Hz (50Hz)	Phase	Voltage	Housing	NEMA Frame	Mounting (3)	Holes / Foot	Service Factor(6) (@50Hz)	F.L. Amps @208-230V/460V	Approx Product Weight (lb) (4)	Drawing Links
<a href="#">MTCP2-001-3BD18</a>	\$226.00	1	1800 (1500)	3	208-230/460V	TEFC cast-iron	143T	F1(F2)	2	1.25 (1.0)	3.61-3.27 / 1.63	41	<a href="#">PDF</a>
<a href="#">MTCP2-001-3BD18C</a>	\$237.00						143TC						<a href="#">PDF</a>
<a href="#">MTCP2-1P5-3BD18</a>	\$286.00	1.5					145T		4		4.92-4.45 / 2.22	56	<a href="#">PDF</a>
<a href="#">MTCP2-1P5-3BD18C</a>	\$295.00						145TC				<a href="#">PDF</a>		
<a href="#">MTCP2-002-3BD18</a>	\$310.00	2					145T		4		6.56-5.93 / 2.97	58.5	<a href="#">PDF</a>
<a href="#">MTCP2-002-3BD18C</a>	\$320.00						145TC				<a href="#">PDF</a>		
<a href="#">MTCP2-003-3BD18</a>	\$538.00	3					182T		2		9.01-8.16 / 4.08	86	<a href="#">PDF</a>
<a href="#">MTCP2-003-3BD18C</a>	\$554.00						182TC				<a href="#">PDF</a>		
<a href="#">MTCP2-005-3BD18</a>	\$558.00	5					184T		4		13.9-12.6 / 6.3	104	<a href="#">PDF</a>
<a href="#">MTCP2-005-3BD18C</a>	\$575.00						184TC				<a href="#">PDF</a>		
<a href="#">MTCP2-7P5-3BD18</a>	\$867.00	7.5					213T		F1(F2)		20.4-18.5 / 9.23	172	<a href="#">PDF</a>
<a href="#">MTCP2-7P5-3BD18C</a>	\$893.00						213TC				<a href="#">PDF</a>		
<a href="#">MTCP2-010-3BD18</a>	\$958.00	10					215T	4			26.9-24.3 / 12.2	193	<a href="#">PDF</a>
<a href="#">MTCP2-010-3BD18C</a>	\$986.00						215TC				<a href="#">PDF</a>		
<a href="#">MTCP2-015-3BD18</a>	\$1,321.00	15					254T	2			40.0-36.2 / 18.1	265	<a href="#">PDF</a>
<a href="#">MTCP2-015-3BD18C</a>	\$1,360.00						254TC				<a href="#">PDF</a>		
<a href="#">MTCP2-020-3BD18</a>	\$1,540.00	20					256T	4			52.4-47.4 / 23.7	304	<a href="#">PDF</a>
<a href="#">MTCP2-020-3BD18C</a>	\$1,586.00						256TC				<a href="#">PDF</a>		
<a href="#">MTCP2-025-3BD18</a>	\$2,128.00	25					284T	2			65.1-58.8 / 29.4	385	<a href="#">PDF</a>
<a href="#">MTCP2-025-3BD18C</a>	\$2,273.00						284TC				<a href="#">PDF</a>		
<a href="#">MTCP2-030-3BD18</a>	\$2,253.00	30					286T	4			78.1-70.6 / 35.3	430	<a href="#">PDF</a>
<a href="#">MTCP2-030-3BD18C</a>	\$2,406.00						286TC				<a href="#">PDF</a>		
<a href="#">MTCP2-040-3BD18</a>	\$2,774.00	40					324T	F1	104-93.7 / 46.8		531	<a href="#">PDF</a>	
<a href="#">MTCP2-050-3BD18</a>	\$3,141.00	50					326T		127-115 / 57.6		578	<a href="#">PDF</a>	
<a href="#">MTCP2-060-3BD18</a>	\$4,172.00	60					364T		158-142 / 71.2		769	<a href="#">PDF</a>	
<a href="#">MTCP2-075-3BD18</a>	\$4,510.00	75					365T		196-177 / 88.7		858	<a href="#">PDF</a>	
<a href="#">MTCP2-100-3BD18</a>	\$5,697.00	100					405T		252-228 / 114		1131	<a href="#">PDF</a>	
<a href="#">MTCP2-125-3BD18</a>	\$6,952.00	125					444T		323-292 / 146		1429	<a href="#">PDF</a>	
<a href="#">MTCP2-150-3BD18</a>	\$8,276.00	150					445T		386-349 / 175		1625	<a href="#">PDF</a>	
<a href="#">MTCP2-200-3BD18</a>	\$9,468.00	200					445/7T		506-458 / 229		2033	<a href="#">PDF</a>	
<a href="#">MTCP2-250-3D18</a>	\$13,867.00	250	449T	F1	2805	2508	<a href="#">PDF</a>						
<a href="#">MTCP2-300-3D18</a>	\$17,993.00	300	449T		3365	2728	<a href="#">PDF</a>						

- 1) Please review the AutomationDirect Terms & Conditions for warranty and service on this product.
- 2) For warranty on motors 50 hp and above, motors must be inspected by an EASA motor repair or service center.
- 3) F1(F2) indicates F1 conduit box mounting location, field convertible to F2 (as shown on dimensional diagram).
- 4) Certain heavy and oversized items can be shipped only via LTL. Check our web site for current shipping method constraints by part number.
- 5) F.L. Amps @ 460V only.
- 6) The service factor changes from 1.25 to 1.0 under the following conditions:
  - When running the motor at 208VAC @ 60Hz
  - When running the motor at 200/400VAC @ 50Hz
  - When used with a VFD



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

T-Frame TEFC Motors – 3-phase Industrial  
Duty – 1–20 hp – 1200 & 3600 rpm

## Motor Specifications – Premium-Efficiency MTCP2 Series 3-phase Motors – 1200 rpm

Part Number <sup>(1)</sup>	Price	HP	Base RPM @60Hz (50Hz)	Phase	Voltage	Housing	NEMA Frame	Mounting <sup>(2)</sup>	Holes / Foot	Service Factor <sup>(4)</sup> (@50Hz)	F.L. Amps @208-230V/460V	Approx Product Weight (lb) <sup>(3)</sup>	Drawing Links
<a href="#">MTCP2-001-3BD12</a>	\$297.00	1	1200 (1000)	3	208-230/460V	TEFC cast-iron	145T	F1(F2)	4	1.25 (1.0)	3.86-3.49 / 1.75	53	<a href="#">PDF</a>
<a href="#">MTCP2-1P5-3BD12</a>	\$473.00	1.5					182T		2		5.22-4.72 / 2.36	91.5	<a href="#">PDF</a>
<a href="#">MTCP2-002-3BD12</a>	\$509.00	2					184T		4		6.59-5.96 / 2.98	100	<a href="#">PDF</a>
<a href="#">MTCP2-003-3BD12</a>	\$652.00	3					213T		2		9.92-8.97 / 4.48	166	<a href="#">PDF</a>
<a href="#">MTCP2-005-3BD12</a>	\$742.00	5					215T		4		16.1-14.5 / 7.27	179	<a href="#">PDF</a>
<a href="#">MTCP2-7P5-3BD12</a>	\$1,202.00	7.5					254T		2		20.8-18.8 / 9.41	247	<a href="#">PDF</a>
<a href="#">MTCP2-010-3BD12</a>	\$1,320.00	10					256T		4		27.8-25.1 / 12.5	258	<a href="#">PDF</a>
<a href="#">MTCP2-015-3BD12</a>	\$1,675.00	15					284T		2		42.9-38.8 / 19.4	366	<a href="#">PDF</a>
<a href="#">MTCP2-020-3BD12</a>	\$1,845.00	20					286T		4		56.5-51.1 / 25.5	419	<a href="#">PDF</a>

1) Please review the AutomationDirect Terms & Conditions for warranty and service on this product.

2) F1(F2) indicates F1 conduit box mounting location, field convertible to F2 (as shown on dimensional diagram).

3) Certain heavy and oversized items can be shipped only via LTL. Check our web site for current shipping method constraints by part number.

4) The service factor changes from 1.25 to 1.0 under the following conditions:

- When running the motor at 208VAC @ 60Hz
- When running the motor at 200/400VAC @ 50Hz
- When used with a VFD

## Motor Specifications – Premium-Efficiency MTCP2 Series 3-phase Motors – 3600 rpm

Part Number <sup>(1)</sup>	Price	HP	Base RPM @60Hz (50Hz)	Phase	Voltage	Housing	NEMA Frame	Mounting <sup>(2)</sup>	Holes / Foot	Service Factor <sup>(4)</sup> (@50Hz)	F.L. Amps @208-230V/460V	Approx Product Weight (lb) <sup>(3)</sup>	Drawing Links
<a href="#">MTCP2-1P5-3BD36</a>	\$254.00	1.5	3600 (3000)	3	208-230/460V	TEFC cast-iron	143T	F1(F2)	2	1.25 (1.0)	4.62-4.18 / 2.09	45.2	<a href="#">PDF</a>
<a href="#">MTCP2-002-3BD36</a>	\$274.00	2					145T		4		6.05-5.48 / 2.74	50.7	<a href="#">PDF</a>
<a href="#">MTCP2-003-3BD36</a>	\$384.00	3					182T	F1	2		6.45-7.64 / 3.82	80.5	<a href="#">PDF</a>
<a href="#">MTCP2-005-3BD36</a>	\$442.00	5					184T		4		13.3-12.0 / 6.01	96	<a href="#">PDF</a>
<a href="#">MTCP2-7P5-3BD36</a>	\$699.00	7.5					213T	F1(F2)	2		20.9-18.9 / 9.45	160	<a href="#">PDF</a>
<a href="#">MTCP2-010-3BD36</a>	\$691.00	10					215T		4		27.0-24.4 / 12.2	180	<a href="#">PDF</a>
<a href="#">MTCP2-015-3BD36</a>	\$1,304.00	15					254T		2		38.8-35.1 / 17.5	261	<a href="#">PDF</a>
<a href="#">MTCP2-020-3BD36</a>	\$1,433.00	20					256T	4	51.1-46.2 / 23.1		297	<a href="#">PDF</a>	

1) Please review the AutomationDirect Terms & Conditions for warranty and service on this product.

2) F1(F2) indicates F1 conduit box mounting location, field convertible to F2 (as shown on dimensional diagram).

3) Certain heavy and oversized items can be shipped only via LTL. Check our web site for current shipping method constraints by part number.

4) The service factor changes from 1.25 to 1.0 under the following conditions:

- When running the motor at 208VAC @ 60Hz
- When running the motor at 200/400VAC @ 50Hz
- When used with a VFD



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

T-Frame TEFC Motors – 3-phase Industrial Duty – 1–300 hp

TC-Frame (C-Face) TEFC Motors – 3-phase Industrial Duty – 1–30 hp

## Performance Data – T & TC Frame 3-phase MTCP2 Motors (460 Volt except as indicated) – 1200, 1800, 3600 rpm

Part Number	HP	NEMA Design	FL RPM	Minimum Speed (rpm)		Current @ 230V/460V (Amps)			Torque (lb-ft)			Maximum Speed (rpm)		FL Efficiency (%)	F.L. Power Factor	Rotor Inertia (lb-ft <sup>2</sup> )
				CT 10:1	VT 20:1	No Load	Full Load	Locked Rotor	Full Load	Locked Rotor	Break-down	CHP(1)	Safe			
<a href="#">MTCP2-001-3BD12</a>	1	B	1160	116	58	2.3/1.5	3.49/1.75	30/15	4.53	8.15	12.00	1800	2400	82.5	0.65	0.118
<a href="#">MTCP2-001-3BD18(C)</a>			1755	175.5	87.75	2.2/1.1	3.27/1.63	30/15	2.99	8.37	11.96	2700	3600	85.5	0.67	0.089
<a href="#">MTCP2-1P5-3BD12</a>	1.5	B	1180	118	59	3.1/1.55	4.72/2.36	40/20	6.67	16.68	24.01	1800	2400	87.5	0.68	0.401
<a href="#">MTCP2-1P5-3BD18(C)</a>			1755	175.5	87.75	2.9/1.45	4.45/2.22	40/20	4.49	12.57	17.51	2700	3600	86.5	0.73	0.105
<a href="#">MTCP2-1P5-3BD36</a>	2	B	3490	348.5	174.25	2.1/1.05	4.18/2.09	40/20	2.26	4.97	7.01	5400	7200	84	0.80	0.043
<a href="#">MTCP2-002-3BD12</a>			1175	118	59	3.7/1.85	5.96/2.98	50/25	8.9	20.47	29.37	1800	2400	88.5	0.71	0.462
<a href="#">MTCP2-002-3BD18(C)</a>	2	B	1755	175.5	87.75	3.9/1.95	5.93/2.97	50/25	5.98	16.15	20.93	2700	3600	86.5	0.73	0.116
<a href="#">MTCP2-002-3BD36</a>			3490	349	174.5	2.5/1.25	5.48/2.74	50/25	3.01	6.92	9.63	5400	7200	85.5	0.80	0.05
<a href="#">MTCP2-003-3BD12</a>	3	B	1175	117.5	58.75	5/2.5	8.97/4.48	64/32	13.3	20.62	31.92	1800	2400	89.5	0.7	0.646
<a href="#">MTCP2-003-3BD18(C)</a>			1755	175.5	87.75	4.6/2.3	8.16/4.08	64/32	9	19.80	28.80	2700	3600	89.5	0.77	0.23
<a href="#">MTCP2-003-3BD36</a>	5	B	3490	350.5	175.25	3.52/1.7	7.64/3.82	64/32	4.49	9.43	15.72	5400	7200	86.5	0.85	0.133
<a href="#">MTCP2-005-3BD12</a>			1175	117.5	58.75	7.1/3.55	14.5/7.27	92/46	22.2	35.52	53.28	1800	2400	89.5	0.72	0.946
<a href="#">MTCP2-005-3BD18(C)</a>	5	B	1755	175.5	87.75	5.4/2.7	12.6/6.3	92/46	15	30.00	42.00	2700	3600	89.5	0.83	0.326
<a href="#">MTCP2-005-3BD36</a>			3490	350.5	175.25	3.1/1.55	12.0/6.01	92/46	7.49	16.48	26.22	5400	7200	88.5	0.88	0.178
<a href="#">MTCP2-7P5-3BD12</a>	7.5	B	1175	117.5	58.75	8.4/4.2	18.8/9.41	127/63.5	33.5	60.30	93.80	1800	2400	91	0.82	2.03
<a href="#">MTCP2-7P5-3BD18(C)</a>			1760	176	88	8.0/4.0	18.5/9.23	127/63.5	22.3	41.26	60.21	2700	3600	91.7	0.83	0.689
<a href="#">MTCP2-7P5-3BD36</a>	10	B	3505	350.5	175.25	6.4/3.2	18.9/9.45	127/63.5	11.2	17.92	33.60	5400	5400	89.5	0.83	11.2
<a href="#">MTCP2-010-3BD12</a>			1175	117.5	58.75	11.6/5.8	25.1/12.5	162/81	44.7	80.46	125.16	1800	2400	91	0.82	2.27
<a href="#">MTCP2-010-3BD18(C)</a>	10	B	1760	176	88	9.8/4.9	24.3/12.2	162/81	29.7	51.98	77.22	2700	3600	91.7	0.84	0.814
<a href="#">MTCP2-010-3BD36</a>			3500	350	175	7.3/3.7	24.4/12.2	162/81	14.9	22.35	41.72	5400	5400	90.2	0.85	0.369
<a href="#">MTCP2-015-3BD12</a>	15	B	1185	118.5	59.25	17/8.5	38.8/19.4	232/116	66.5	96.43	152.95	1800	2400	91.7	0.79	4.09
<a href="#">MTCP2-015-3BD18(C)</a>			1765	176.5	88.25	15/7.5	36.2/18.1	232/116	44.6	84.74	120.42	2700	3600	92.4	0.84	1.89
<a href="#">MTCP2-015-3BD36</a>	20	B	3540	354.5	177.25	9.8/4.9	35.1/17.5	232/116	22.2	37.74	55.50	5400	5400	91	0.88	1.06
<a href="#">MTCP2-020-3BD12</a>			1185	118.5	59.25	49.2/24.6	51.1/25.5	290/145	88.6	124.04	194.92	1800	2400	91.7	0.80	5
<a href="#">MTCP2-020-3BD18(C)</a>	20	B	1765	176.5	88.25	18/9	47.4/23.7	290/145	59.5	107.10	148.75	2700	3600	93	0.85	2.33
<a href="#">MTCP2-020-3BD36</a>			3540	354	177	46.2/23.1	46.2/23.1	290/145	29.7	47.52	68.31	5400	5400	91	0.89	1.26
<a href="#">MTCP2-025-3BD18(C)</a>	25	B	1770	177	88.5	21.2/10.6	58.8/29.4	365/182.5	74.2	111.30	178.08	2700	2700	93.6	0.85	3.36
<a href="#">MTCP2-030-3BD18(C)</a>	30	B	1770	177	88.5	24/12	70.6/35.3	435/217.5	89	133.50	213.60	2700	2700	93.6	0.85	3.83
<a href="#">MTCP2-040-3BD18</a>	40	B	1775	177.5	88.75	34/17	93.7/46.8	580/290	118	188.80	306.80	2700	2700	94.1	0.85	6.11
<a href="#">MTCP2-050-3BD18</a>	50	B	1775	177.5	88.75	41/20.5	115/57.6	725/362.5	148	236.80	384.80	2700	2700	94.5	0.86	6.89
<a href="#">MTCP2-060-3BD18</a>	60	B	1780	178	89	56/28	142/71.2	870/435	177	362.85	442.50	2700	2700	95	0.83	14.7
<a href="#">MTCP2-075-3BD18</a>	75	B	1780	178	89	74/37	177/88.7	1085/542.5	221	397.80	508.30	2700	2700	95.4	0.83	17.5
<a href="#">MTCP2-100-3BD18</a>	100	B	1785	178.5	89.25	70/35	228/114	1450/725	294	470.40	735.00	2700	2700	95.4	0.86	31.2
<a href="#">MTCP2-125-3BD18</a>	125	B	1790	179	89.5	104/52	292/146	1815/907	367	587.20	880.80	2700	2700	95.4	0.84	40.1
<a href="#">MTCP2-150-3BD18</a>	150	B	1790	179	89.5	113/56.5	349/175	2170/1085	440	704.00	1056.00	2700	2700	95.8	0.84	48.5
<a href="#">MTCP2-200-3BD18</a>	200	B	1790	179	89.5	144/72	458/229	2900/1450	587	997.90	1467.50	2700	2250	96.2	0.85	64.3
<a href="#">MTCP2-250-3D18</a>	250	B	1790	179	89.5	91.9 <sup>2</sup>	280 <sup>2</sup>	1825 <sup>2</sup>	773	1546.00	2009.80	2700	2250	96.2	0.87	78.8
<a href="#">MTCP2-300-3D18</a>	300	B	1790	179	89.5	103 <sup>2</sup>	336 <sup>2</sup>	2200 <sup>2</sup>	880	1760.00	2200.00	2700	2250	96.2	0.87	94.1

1) Maximum Constant HP RPM is for direct coupled loads.

2) Current @460V (Amps)



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

## Premium Efficiency TEFC T-Frame 3-phase Motor C-Flange Kits – 1 to 300 hp

We stock Premium Efficiency NEMA cast-iron T-frame motors from 1–300 hp, and TC-frame motors from 1–30 hp.

We also offer IronHorse cast-iron C-flange kits which can be used for C-face mounting of our 1–300 hp IronHorse MTCP2 Premium Efficiency cast-iron T-frame motors.

**C-faces must be installed by an EASA motor shop in order to maintain the motor warranty.**



MTCP2 Premium-Efficiency T-frame 3-phase Motor C-Flange Kits					
Part Number (1)	Price	Fits Frame	Fits Motor Number	Motor HP	Product Weight (lb) (2)
<a href="#"><u>MTAP2-CFACE-140TC</u></a>	\$29.00	143T & 145T	<a href="#"><u>MTCP2-001-3BD12</u></a> <a href="#"><u>MTCP2-001-3BD18</u></a> <a href="#"><u>MTCP2-1P5-3BD18</u></a> <a href="#"><u>MTCP2-1P5-3BD36</u></a> <a href="#"><u>MTCP2-002-3BD18</u></a> <a href="#"><u>MTCP2-002-3BD36</u></a>	1 1 1-1/2 1-1/2 2 2	5.62
<a href="#"><u>MTAP2-CFACE-180TC</u></a>	\$40.00	182T & 184T	<a href="#"><u>MTCP2-1P5-3BD12</u></a> <a href="#"><u>MTCP2-002-3BD12</u></a> <a href="#"><u>MTCP2-003-3BD18</u></a> <a href="#"><u>MTCP2-003-3BD36</u></a> <a href="#"><u>MTCP2-005-3BD18</u></a> <a href="#"><u>MTCP2-005-3BD36</u></a>	1-1/2 2 3 3 5 5	10.36
<a href="#"><u>MTAP2-CFACE-210TC</u></a>	\$56.00	213T & 215T	<a href="#"><u>MTCP2-003-3BD12</u></a> <a href="#"><u>MTCP2-005-3BD12</u></a> <a href="#"><u>MTCP2-7P5-3BD18</u></a> <a href="#"><u>MTCP2-7P5-3BD36</u></a> <a href="#"><u>MTCP2-010-3BD18</u></a> <a href="#"><u>MTCP2-010-3BD36</u></a>	3 5 7-1/2 7-1/2 10 10	12.68
<a href="#"><u>MTAP2-CFACE-250TC</u></a>	\$96.00	254T & 256T	<a href="#"><u>MTCP2-7P5-3BD12</u></a> <a href="#"><u>MTCP2-010-3BD12</u></a> <a href="#"><u>MTCP2-015-3BD18</u></a> <a href="#"><u>MTCP2-015-3BD36</u></a> <a href="#"><u>MTCP2-020-3BD18</u></a> <a href="#"><u>MTCP2-020-3BD36</u></a>	7-1/2 10 15 15 20 20	31.20
<a href="#"><u>MTAP2-CFACE-280TC</u></a>	\$122.00	284T & 286T	<a href="#"><u>MTCP2-015-3BD12</u></a> <a href="#"><u>MTCP2-020-3BD12</u></a> <a href="#"><u>MTCP2-025-3BD18</u></a> <a href="#"><u>MTCP2-030-3BD18</u></a>	15 20 25 30	31.20
<a href="#"><u>MTAP2-CFACE-320TC</u></a>	\$168.00	324T & 326T	<a href="#"><u>MTCP2-040-3BD18</u></a> <a href="#"><u>MTCP2-050-3BD18</u></a>	40 50	47.40
<a href="#"><u>MTAP2-CFACE-360TC</u></a>	\$239.00	364T & 365T	<a href="#"><u>MTCP2-060-3BD18</u></a> <a href="#"><u>MTCP2-075-3BD18</u></a>	60 75	48.70
<a href="#"><u>MTAP2-CFACE-400TC</u></a>	\$366.00	405T	<a href="#"><u>MTCP2-100-3BD18</u></a>	100	132.17
<a href="#"><u>MTAP2-CFACE-444TC</u></a>	\$389.00	444T & 445T	<a href="#"><u>MTCP2-125-3BD18</u></a> <a href="#"><u>MTCP2-150-3BD18</u></a>	125 150	137.44
<a href="#"><u>MTAP2-CFACE-447TC</u></a>	\$389.00	445/7T	<a href="#"><u>MTCP2-200-3BD18</u></a>	200	134.83
<a href="#"><u>MTAP2-CFACE-449TC</u></a>	\$839.00	449T	<a href="#"><u>MTCP2-250-3D18</u></a> <a href="#"><u>MTCP2-300-3D18</u></a>	250 300	162.50

1) Please review the AutomationDirect Terms & Conditions for warranty and service on this product.

2) Certain heavy and oversized items can be shipped only via LTL.

Check our web site for current shipping method constraints by part number.



# MTCP2 Premium-Efficiency Cast-Iron 3-phase AC Motors

## Premium Efficiency TEFC 3-phase Motor Replacement Parts – 1 to 300 hp

We stock MTCP2 Premium Efficiency NEMA cast-iron T-frame motors from 1–300 hp, and TC-frame motors from 1–30 hp.

We also offer IronHorse junction boxes, TEFC fans, and TEFC fan shrouds as direct replacement parts for these MTCP2 motors.

These replacement parts are field installable. Instructions included.



MTCP2 Premium-Efficiency 3-phase Motor Replacement Parts						
Part Number <sup>(1)</sup>	Price	Description <sup>(2)(3)(4)</sup>	Fits Frame	Fits PE Motor Number <sup>(1)</sup>	Motor HP	Product Wt. (lb)
<a href="#">MTAP2-FAN-140</a>	\$40.00	Replacement Fan	143 & 145	<a href="#">MTCP2-001-3BD12</a>	1	0.029
<a href="#">MTAP2-SHROUD-140</a>	\$34.00	Replacement Fan Shroud		<a href="#">MTCP2-001-3BD18(C)</a>	1	1.04
				<a href="#">MTCP2-1P5-3BD18(C)</a>	1-1/2	
				<a href="#">MTCP2-1P5-3BD36</a>	1-1/2	
<a href="#">MTAP2-JBOX-140</a>	\$34.00	Replacement Junction Box		<a href="#">MTCP2-002-3BD18(C)</a>	2	2.54
				<a href="#">MTCP2-002-3BD36</a>	2	
<a href="#">MTAP2-FAN-180</a>	\$40.00	Replacement Fan	182 & 184	<a href="#">MTCP2-1P5-3BD12</a>	1-1/2	0.053
<a href="#">MTAP2-SHROUD-180</a>	\$48.00	Replacement Fan Shroud		<a href="#">MTCP2-002-3BD12</a>	2	2.23
				<a href="#">MTCP2-003-3BD18(C)</a>	3	
				<a href="#">MTCP2-003-3BD36</a>	3	
<a href="#">MTAP2-JBOX-180</a>	\$49.50	Replacement Junction Box		<a href="#">MTCP2-005-3BD18(C)</a>	5	3.28
				<a href="#">MTCP2-005-3BD36</a>	5	
<a href="#">MTAP2-FAN-210-2</a>	\$44.50	Replacement Fan (for 2-pole motors)	213 & 215	<a href="#">MTCP2-7P5-3BD36</a>	7-1/2	0.075
				<a href="#">MTCP2-010-3BD36</a>	10	
<a href="#">MTAP2-FAN-210</a>	\$42.50	Replacement Fan (4&6-pole)		<a href="#">MTCP2-003-3BD12</a>	3	0.075
				<a href="#">MTCP2-005-3BD12</a>	5	
<a href="#">MTAP2-SHROUD-210</a>	\$49.50	Replacement Fan Shroud		<a href="#">MTCP2-7P5-3BD18(C)</a>	7-1/2	4.98
<a href="#">MTAP2-JBOX-210</a>	\$49.50	Replacement Junction Box		<a href="#">MTCP2-010-3BD18(C)</a>	10	3.28
<a href="#">MTAP2-FAN-250-2</a>	\$72.00	Replacement Fan (for 2-pole motors)	254 & 256	<a href="#">MTCP2-015-3BD36</a>	15	0.090
				<a href="#">MTCP2-020-3BD36</a>	20	
<a href="#">MTAP2-FAN-250</a>	\$72.00	Replacement Fan (4&6-pole)		<a href="#">MTCP2-7P5-3BD12</a>	7-1/2	0.104
				<a href="#">MTCP2-010-3BD12</a>	10	
<a href="#">MTAP2-SHROUD-250</a>	\$83.00	Replacement Fan Shroud		<a href="#">MTCP2-015-3BD18(C)</a>	15	8.27
<a href="#">MTAP2-JBOX-250</a>	\$83.00	Replacement Junction Box		<a href="#">MTCP2-020-3BD18(C)</a>	20	8.16
<a href="#">MTAP2-FAN-280</a>	\$99.00	Replacement Fan	284 & 286	<a href="#">MTCP2-015-3BD12</a>	15	0.090
<a href="#">MTAP2-SHROUD-280</a>	\$123.00	Replacement Fan Shroud		<a href="#">MTCP2-020-3BD12</a>	20	10.03
				<a href="#">MTCP2-025-3BD18(C)</a>	25	
<a href="#">MTAP2-JBOX-280</a>	\$149.00	Replacement Junction Box		<a href="#">MTCP2-030-3BD18(C)</a>	30	8.16
<a href="#">MTAP2-FAN-320</a>	\$137.00	Replacement Fan	324 & 326			0.126
<a href="#">MTAP2-SHROUD-320</a>	\$149.00	Replacement Fan Shroud		<a href="#">MTCP2-040-3BD18(C)</a>	40	12.50
				<a href="#">MTCP2-050-3BD18(C)</a>	50	23.59
<a href="#">MTAP2-JBOX-320</a>	\$149.00	Replacement Junction Box				
<a href="#">MTAP2-FAN-360</a>	\$223.00	Replacement Fan	364 & 365			0.126
<a href="#">MTAP2-SHROUD-360</a>	\$229.00	Replacement Fan Shroud		<a href="#">MTCP2-060-3BD18(C)</a>	60	13.76
				<a href="#">MTCP2-075-3BD18(C)</a>	75	21.05
<a href="#">MTAP2-JBOX-360</a>	\$280.00	Replacement Junction Box				
<a href="#">MTAP2-FAN-400</a>	\$261.00	Replacement Fan	405			0.150
<a href="#">MTAP2-SHROUD-400</a>	\$280.00	Replacement Fan Shroud		<a href="#">MTCP2-100-3BD18(C)</a>	100	16.67
						32.74
<a href="#">MTAP2-JBOX-400</a>	\$280.00	Replacement Junction Box				
<a href="#">MTAP2-FAN-440</a>	\$286.00	Replacement Fan	444 & 445 & 447	<a href="#">MTCP2-125-3BD18</a>	125	0.150
<a href="#">MTAP2-SHROUD-440</a>	\$313.00	Replacement Fan Shroud		<a href="#">MTCP2-150-3BD18</a>	150	17.97
				<a href="#">MTCP2-200-3BD18</a>	200	36.49
<a href="#">MTAP2-JBOX-440</a>	\$313.00	Replacement Junction Box				
<a href="#">MTAP2-FAN-449</a>	\$419.00	Replacement Fan	449	<a href="#">MTCP2-250-3D18</a>	250	0.205
<a href="#">MTAP2-FAN-449-1</a>	\$415.00	Replacement Fan		<a href="#">MTCP2-300-3D18</a>	300	0.174
<a href="#">MTAP2-JBOX-449</a>	\$555.00	Replacement Junction Box		<a href="#">MTCP2-250-3D18</a>	250	22.27
<a href="#">MTAP2-SHROUD-449</a>	\$580.00	Replacement Fan Shroud		<a href="#">MTCP2-300-3D18</a>	300	36.49

- 1) These MTAP2 replacement components fit only MTCP2 Premium Efficiency motors.
- 2) Replacement Fans include fan and snap ring.
- 3) Replacement Fan Shrouds include shroud, bolts w/washers, and rubber plug.
- 4) Replacement Junction Boxes include gasketed base & cover assembly, base gasket, and base bolts.



# AC Motor Selection – IronHorse® General Purpose Motors

IronHorse® 3-Phase Motor Selection					
Motor Series	MTR2/MTRP	MTRJ/MTRJP	MTDP	MTSP/MTSN	MTCP2
Paint Color	Black	Black	Blue	Stainless	Gray
Main Characteristics	General Purpose Rolled Steel	Jet Pump	Rolled Steel Open Drip Proof	Stainless Steel Premium Efficiency IP69K	Cast-Iron Hazardous Duty
Electrical Characteristics					
Horsepower range	1/3 - 3	1/3 - 3	1 - 50	1 - 20	1 - 300(T) 1 - 30(TC)
Base speed	1800; 3600	3600	1800; 3600	1200; 1800; 3600	1200; 1800; 3600
Standard Voltage	208-230/460 VAC; 230/460 VAC	208-230/460 VAC; 230/460 VAC	208-230/460 VAC	208-230/460 VAC	208-230/460 VAC; 460VAC
Phase / Base Frequency (Hz)	3-phase / 60 Hz				
Service Factor	1.15	1.15	1.15 (sine), 1.0 (drive)		1.25 (1-200) 1.15 (250-300) 1.0 (all w/ drive)
Design Code (NEMA)	B				
Insulation Class	Class F				
Insulation System	Dip and Bake	Dip and Bake Twice	VPI	Dip and Bake	Vacuum Impregnation
Duty Cycle	Continuous				
Thermal protection	None				
Hazard Classification	None			Class 1 / Div 2	
Mechanical Characteristics					
Frame size	56C or HC - 326T	56J	56C - 326T	56C - 256TC	143T/TC - 449T
Enclosure	ODP / TEFC	TEFC	ODP / TEFC	TEFC / TENV	TEFC
Enclosure Rating	IP43		IP23	IP69K	IP55
Frame material	Rolled steel		Rolled steel	304 Stainless steel	Cast iron
End bracket material	Aluminum	Aluminum	≤256 frame- Aluminum >256- Cast iron	304 Stainless steel	Cast iron
Junction box material	Steel	Steel	Steel	304 Stainless steel	Cast iron
Fan guard material	Steel	Steel	N/a	304 Stainless steel	Steel
Fan material	Polypropylene plastic	Plastic	N/a	Heat-Resistant Polyethylene	Plastic
Lead termination	Junction Box				
standard mounting	C-face with removable rigid base		Rigid base	C-face round body and C-face with rigid base	Rigid base, c-face with rigid base (1-100 hp)
Drive end shaft slinger	Yes	Yes	None	Yes	Yes
Bearings	Ball				1-300 hp - 2p, 1-75 hp - 4p & 6p: Ball 100-300 hp - 4p & 6p: Roller
Grease	Mobil Polyrex EM		NS7 ENS	Mobil Polyrex EM	
Standard junction box assembly position	F1				F1 (field convertible F2)
Performance Characteristics					
Constant Torque speed range	4:1	4:1	10:1	10:1	10:1
Variable Torque speed range	10:1	10:1	20:1	20:1	20:1
Constant Horsepower speed range	1.5:1	1.5:1	1.5:1	1.5:1	1.5:1
Temperature rise	B				
Encoder provisions	None				
Other Characteristics					
Warranty*	2 years	2 years	2 years	1 year	2 years
Agency Approvals **	CSA, CE	CSA,CE	CSA	NEMA, CSA, UR, CE, BISCC	CSA, ISO9001, CE

\* See Terms and Conditions for motor warranty explanation.

1) For warranty on IronHorse motors below 50hp, warranty service can be arranged through AutomationDirect.

2) For warranty on IronHorse motors 50hp and above, motors must be inspected by a local EASA motor repair or service center; (see AutomationDirect Terms & Conditions).

\*\* To obtain the most current agency approval information, see the Agency Approval Checklist on the specific part number's web page.

\*\*\* 56HC motors are capable of 56C C-face mounting, and are also compatible with 56, 143T, and 145T foot mounting dimensions.