

# CAPTRON Capacitive Switches

## Overview

SENSORswitches are capacitive pushbuttons that are activated without pressure, using a hand or other parts of the body. The buttons have a determinate sensing distance, which may be altered by varying the approach speed and/or damping factor. A quickly approaching finger will achieve a higher sensing distance than a slowly approaching finger. A hand, with its larger damping surface, will achieve a greater sensing distance than a finger at the same speed. The sensitivity of the buttons is specified by the electronic circuit and cannot be changed. All sensors are checked for consistent sensitivity values, which have been determined by long-standing experience.



## Switch Type

### Static

- The output signal is continuously on as long as the sensor area is activated.

### Dynamic

- The output signal length is limited to x milliseconds when the sensor area is activated.


### Toggle

- The output signal turns on when the sensor area is activated and stays on until the sensor area is activated again.

## LED Control


### Semi-Automatic

Semi-Automatic (4-Pin) LED1 can be controlled separately. Ideal for when the system designer would like to display a flashing signal to prompt the user to activate and or touch the switch.




### Manual

Manual (5-Pin) LED1 and LED2 can be controlled separately. Ideal for use when the user would like to show optical feedback acting like a signal indicator (e.g. CDL series or CML series indicator lights).



### Automatic

Automatic (3-Pin) LED1 turns off and the LED2 lights up when the operating surface is touched. Ideal choice for all Human-Machine Interface (HMI) applications that require an intuitive and clearly visible status display.



# CAPTRON 22mm IP69K Capacitive Switches



**CHT1-158X-XX**  
(Hygienic)



**CHT1-XXXX-XX-CPM20**



**CHT1-159X-XX**



**CHT3-456X-X-XXXXX**



**CHT3-456X-X-XXXX**

| 22mm IP69K Capacitive Switches, PNP, N.O. |       |                            |                |                |                |             |                       |                    |                     |               |                     |
|-------------------------------------------|-------|----------------------------|----------------|----------------|----------------|-------------|-----------------------|--------------------|---------------------|---------------|---------------------|
| Part Number                               | Price | LED Color<br>(Idle/Active) | Switch<br>Type | Diameter<br>mm | LED Control    | Legend      | Symbol<br>Illuminated | Connection<br>(M8) | Agency<br>Approvals | Weight<br>lbs | Drawing<br>Link     |
| <a href="#">CHT1-158B-30</a>              |       | red/green                  | Static         | 40.0 mm        | Manual         | -           | No                    | 5-pole             | CE, CSA             | 0.09          | <a href="#">PDF</a> |
| <a href="#">CHT1-158B-30-CPM20</a>        |       |                            |                | 28.5 mm        |                | -           |                       |                    |                     | 0.07          | <a href="#">PDF</a> |
| <a href="#">CHT1-158P-30</a>              |       |                            |                | 40.0 mm        | Semi-automatic | -           |                       | 4-pole             |                     | 0.08          | <a href="#">PDF</a> |
| <a href="#">CHT1-158P-30-CPM20</a>        |       |                            |                |                |                | -           |                       |                    |                     | 0.06          | <a href="#">PDF</a> |
| <a href="#">CHT1-159B-29</a>              |       |                            |                | 28.5 mm        | Manual         | START       |                       | 5-pole             |                     | 0.07          | <a href="#">PDF</a> |
| <a href="#">CHT1-159B-30</a>              |       |                            |                |                |                | -           |                       |                    |                     | 0.06          | <a href="#">PDF</a> |
| <a href="#">CHT1-159P-29</a>              |       |                            |                |                | Semi-automatic | START       |                       | 4-pole             |                     | 0.05          | <a href="#">PDF</a> |
| <a href="#">CHT1-159P-30</a>              |       |                            |                |                |                | -           |                       |                    |                     | 0.05          | <a href="#">PDF</a> |
| <a href="#">CHT12-159B-30</a>             |       |                            | Toggle         |                | Manual         | -           |                       | 5-pole             |                     | 0.06          | <a href="#">PDF</a> |
| <a href="#">CHT12-159B-64</a>             |       |                            |                |                |                | START/STOP  |                       |                    |                     | 0.06          | <a href="#">PDF</a> |
| <a href="#">CHT12-159P-30</a>             |       |                            |                |                | Semi-automatic | -           |                       | 4-pole             |                     | 0.05          | <a href="#">PDF</a> |
| <a href="#">CHT12-159P-64</a>             |       |                            |                |                |                | START/STOP  |                       |                    |                     | 0.05          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-29-TGSR</a>         |       |                            | Dynamic        | 60.0 mm        | Manual         | START       |                       | 5-pole             |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-29-TGSRs</a>        |       |                            | Static         |                |                | START       |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-30-TGSR</a>         |       |                            | Dynamic        |                |                | -           |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-30-TGSRs</a>        |       |                            | Static         |                |                | -           |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-H-TGSR</a>          |       |                            | Dynamic        |                |                | Hand Symbol |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456B-H-TGSRs</a>         |       |                            | Static         |                |                | Hand Symbol |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-29-TGSR</a>         |       |                            | Dynamic        |                | Semi-automatic | START       |                       | 4-pole             |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-29-TGSRs</a>        |       |                            | Static         |                |                | START       |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-30-TGSR</a>         |       |                            | Dynamic        |                |                | -           |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-30-TGSRs</a>        |       |                            | Static         |                |                | -           |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-H-TGSR</a>          |       |                            | Dynamic        |                |                | Hand Symbol |                       |                    |                     | 0.22          | <a href="#">PDF</a> |
| <a href="#">CHT3-456P-H-TGSRs</a>         |       |                            | Static         |                |                | Hand Symbol |                       |                    |                     | 0.22          | <a href="#">PDF</a> |

Purchase cable separately.

**CAPTRON**

# 50 and 60mm IP69K Capacitive Switches



CHT3-15XX-XX-XXXX



CHT4-25XX-XX-XXXX



CHT4-25XX-X-XXXX

| *50 and 60mm IP69K Capacitive Switches (Require AR3 or AR4 Cover Ring) |       |                            |                |                      |                                     |                    |                     |                       |                    |                     |               |                     |                     |
|------------------------------------------------------------------------|-------|----------------------------|----------------|----------------------|-------------------------------------|--------------------|---------------------|-----------------------|--------------------|---------------------|---------------|---------------------|---------------------|
| Part Number                                                            | Price | LED Color<br>(Idle/Active) | Switch<br>Type | Barrel<br>Size<br>mm | Diameter<br>(w/Cover<br>ring)<br>mm | LED<br>Control     | Legend              | Symbol<br>Illuminated | Connection<br>(M8) | Agency<br>Approvals | Weight<br>lbs | Drawing<br>Link     |                     |
| <a href="#">CHT3-15XB-29-TGSR</a>                                      |       | red/green                  | Dynamic        | 50.0<br>mm           | 88.0 mm                             | Manual             | START               | No                    | 5-pole             | CE, CSA             | 0.18          | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XB-29-TGSRs</a>                                     |       |                            | Static         |                      |                                     |                    | START               |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XB-30-TGSR</a>                                      |       |                            | Dynamic        |                      |                                     |                    | -                   |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XB-30-TGSRs</a>                                     |       |                            | Static         |                      |                                     |                    | -                   |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XB-H-TGSR</a>                                       |       |                            | Dynamic        |                      |                                     |                    | Hand Symbol         |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XB-H-TGSRs</a>                                      |       |                            | Static         |                      |                                     |                    | Hand Symbol         |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT3-15XP-29-TGSR</a>                                      |       |                            | Dynamic        |                      |                                     | Semi-<br>automatic | START               |                       | 4-pole             |                     |               | PDF                 |                     |
| <a href="#">CHT3-15XP-29-TGSRs</a>                                     |       |                            | Static         |                      |                                     |                    | START               |                       |                    |                     |               |                     | <a href="#">PDF</a> |
| <a href="#">CHT3-15XP-30-TGSR</a>                                      |       |                            | Dynamic        |                      |                                     |                    | -                   |                       |                    |                     |               |                     | <a href="#">PDF</a> |
| <a href="#">CHT3-15XP-30-TGSRs</a>                                     |       |                            | Static         |                      |                                     |                    | -                   |                       |                    |                     |               |                     | <a href="#">PDF</a> |
| <a href="#">CHT3-15XP-H-TGSR</a>                                       |       |                            | Dynamic        |                      |                                     |                    | Hand Symbol         |                       |                    |                     |               |                     | <a href="#">PDF</a> |
| <a href="#">CHT3-15XP-H-TGSRs</a>                                      |       |                            | Static         |                      |                                     |                    | Hand Symbol         |                       |                    |                     |               |                     | <a href="#">PDF</a> |
| <a href="#">CHT4-25XB-29-TGSR</a>                                      |       |                            | Dynamic        | 60.0<br>mm           | 100.0 mm                            | Manual             | START               | 5-pole                | PDF                |                     |               |                     |                     |
| <a href="#">CHT4-25XB-30-TGSR</a>                                      |       |                            |                |                      |                                     |                    | -                   |                       |                    |                     |               | <a href="#">PDF</a> |                     |
| <a href="#">CHT4-25XB-H-TGSR</a>                                       |       | Hand Symbol                |                |                      |                                     |                    | <a href="#">PDF</a> |                       |                    |                     |               |                     |                     |
| <a href="#">CHT4-25XP-29-TGSR</a>                                      |       | Semi-<br>automatic         |                |                      |                                     | START              | 4-pole              |                       |                    | <a href="#">PDF</a> |               |                     |                     |
| <a href="#">CHT4-25XP-30-TGSR</a>                                      |       |                            |                |                      |                                     | -                  |                     |                       |                    | <a href="#">PDF</a> |               |                     |                     |
| <a href="#">CHT4-25XP-H-TGSR</a>                                       |       |                            |                |                      |                                     | Hand Symbol        |                     |                       |                    | <a href="#">PDF</a> |               |                     |                     |

\*Purchase cable separately.

# CAPTRON Cover Rings and Indicator Lights

| AR3 Cover Ring (Fits All CHT3 Switches) |       |        |                                                                                     |
|-----------------------------------------|-------|--------|-------------------------------------------------------------------------------------|
| Part Number                             | Price | Color  | Image                                                                               |
| <a href="#"><u>AR3-1X0</u></a>          |       | Red    |    |
| <a href="#"><u>AR3-1X1</u></a>          |       | Green  |    |
| <a href="#"><u>AR3-1X5</u></a>          |       | Yellow |   |
| <a href="#"><u>AR3-1X6</u></a>          |       | Black  |  |

| AR4 Cover Ring (Fits All CHT4 Switches) |       |        |                                                                                       |
|-----------------------------------------|-------|--------|---------------------------------------------------------------------------------------|
| Part Number                             | Price | Color  | Image                                                                                 |
| <a href="#"><u>AR4-BX0</u></a>          |       | Red    |    |
| <a href="#"><u>AR4-BX1</u></a>          |       | Green  |    |
| <a href="#"><u>AR4-BX5</u></a>          |       | Yellow |   |
| <a href="#"><u>AR4-BX6</u></a>          |       | Black  |  |

| *IP6K 22mm CDL and CML Series IP69K Indicator Lights |       |                                                       |                             |                        |              |                     |                              |                               |                  |            |                            |
|------------------------------------------------------|-------|-------------------------------------------------------|-----------------------------|------------------------|--------------|---------------------|------------------------------|-------------------------------|------------------|------------|----------------------------|
| Part Number                                          | Price | Color                                                 | Material                    | Supply Voltage         | Load Current | Current Consumption | Operating Temperature        | Storage Temperature           | Agency Approvals | Weight lbs | Drawing Links              |
| <a href="#"><u>CDL1-158-30-GR</u></a>                |       | Red/green                                             | Plastic And Stainless Steel | 24VDC<br>[21.6~26.4 V] | Max<br>400mA | Max 20mA<br>@24V    | -20 to 50°C<br>[-4 to 122°F] | -25 to 55°C<br>[-13 to 131°F] | CE, CSA          | 0.08       | <a href="#"><u>PDF</u></a> |
| <a href="#"><u>CDL1-159-30-GR</u></a>                |       |                                                       | Plastic And Aluminum        |                        |              |                     |                              |                               |                  | 0.05       | <a href="#"><u>PDF</u></a> |
| <a href="#"><u>CML1-158-30</u></a>                   |       | Red/yellow/<br>green/blue/<br>white/orange/<br>violet | Plastic And Stainless Steel |                        |              | Max 30mA<br>@24V    |                              |                               |                  | 0.08       | <a href="#"><u>PDF</u></a> |
| <a href="#"><u>CML1-159-30</u></a>                   |       |                                                       | Plastic And Aluminum        |                        |              |                     |                              |                               |                  | 0.05       | <a href="#"><u>PDF</u></a> |

\*Purchase cable separately.



[CDL1-158-30-GR](#)  
[CML1-158-30](#)  
(Hygienic)



[CDL1-159-30-GR](#)  
[CML1-159-30](#)





# Capacitive Switches Specifications

| Specifications                            |                     |          |                          |              |                     |                            |                            |           |                                                                                 |
|-------------------------------------------|---------------------|----------|--------------------------|--------------|---------------------|----------------------------|----------------------------|-----------|---------------------------------------------------------------------------------|
| Part Number                               | Supply Voltage      | Output   | Output Pulse             | Load Current | Current Consumption | Operating Temperature      | Storage Temperature        | IP Rating | Material                                                                        |
| <a href="#"><u>CHT1</u></a>               | 10–30 VDC           | PNP-N.O. | Continuous when actuated | Max 400mA    | Max 20mA @24V       | -30 to 70°C [-22 to 158°F] | -35 to 75°C [-31 to 167°F] | IP69K     | CHT1-158 Plastic and Stainless Steel<br>CHT1-159 and CHT12 Plastic and Aluminum |
| <a href="#"><u>CHT12</u></a>              |                     |          | Toggle                   |              |                     |                            |                            |           |                                                                                 |
| <a href="#"><u>CHTX-XXXX-XX-TGSR</u></a>  | 24VDC (21.6–26.4 V) |          | Approx. 300ms            |              | Max 30mA @24V       | -30 to 80°C [-22 to 176°F] | -35 to 85°C [-31 to 185°F] |           |                                                                                 |
| <a href="#"><u>CHTX-XXXX-XX-TGSRS</u></a> |                     |          | Continuous when actuated |              |                     | 0 to 55°C [32 to 131°F]    |                            |           |                                                                                 |