SHIMPO Handheld Tachometers

DT-200LR Series Combination Laser Tachometers

The DT-200LR Series Combination Contact/Non-Contact Laser Handheld Tachometers enable precise non-contact RPM measurement up to 20 feet away. The Series DT-200LR digital tachometers incorporate laser technology yet retain rugged construction and reliable quality components. These instruments feature a field-upgradeable contact adapter for linear rate measure, conveniently allowing both non-contact and contact measurements. These user friendly, value-packed units feature memory storage, quick adjustment units knob, length functions, retrieval of last, maximum and minimum values. Each unit comes standard with a free NIST certificate*. Units are available with an LCD or vibrant red LED display.

Features

- Outstanding accuracy for the strictest applications
- Sophisticated laser beam detection to 20 feet provides operator safety during testing
- Rugged die-cast aluminum housing enables usage in the harshest conditions
- Wide field selection of units in both instantaneous rate as well as totalized length satisfies a multitude of user requirements
- Large 5-digit display aids user visibility
- Expansive 10 measurement memory capacity allows quick retrieval of stored data plus additional last, maximum & minimum values
- Long battery life (25-40 hrs. continuous use)
- Compact, ergonomic design allows easy grip
- Rear threaded inserts (1/4-20 x 5/16 in.) provide additional mounting options
- Available display options of either LCD or vibrant, bright red LED
- CE compliant. Includes free N.I.S.T. certificate.*
- 2-year warranty

Included Accessories

Each DT-200LR Series Handheld Tachometer includes a contact adapter, (2) 1/2-inch cone adapters, a 1/2-inch funnel adapter, a 6-inch circumference measuring wheel, a 3.5-inch extension shaft, 1-inch x 7.75-inch reflective tape, (2) AA alkaline batteries and carrrying case. Additional and replacement accessories can be found on the following page.



DT-205LR

| DT-200LR Series Handheld Tachometers | | | |
|--------------------------------------|---|-------|--|
| Part Number | Description | Price | |
| DT-205LR | Handheld tachometer, non-contact / contact, 5-digit LCD display | | |
| DT-207LR | Handheld tachometer, non-contact / contact, 5-digit LED display | | |

* NIST certificates are valid one year from the date the unit ships from Shimpo to AutomationDirect. In order to maintain stock levels for immediate availability, up to six-month "shelf time" may have elapsed before a unit is received by the customer.

Calibration services are not available from AutomationDirect. Contact Shimpo Instruments at (800) 237-7079 or www.shimpoinst.com/contactus for any calibration needs.



SHIMPO Handheld Tachometers

DT-200LR Series Combination Laser Tachometers

| DT-200LR Series Specifications | | | | |
|--------------------------------|---|--|--|--|
| Display Range | 6 - 99,999 RPM | | | |
| Accuracy | ±1 RPM @ 6 - 8,300 RPM ±2 RPM @ 8,300 - 25,000 RPM ±0.006% of reading ±1 digit (±6 RPM max.) 25,000 - 99,999 RPM | | | |
| Display | DT-205A — 5-digit 0.47 in. (12 mm) high LCD DT-207A — 5-digit 0.40 in. (10 mm) high LED | | | |
| Measuring Units | RPM (using included contact adapter) YPM, mPM, FPM, IPM, and Length: YRD, m, FT and IN | | | |
| Measuring Distance | Use wheel with 200L adapter 1 in. (25.4 mm) to 20 feet (6m) | | | |
| Memory System | 13 readings are stored in memory and retained for 5 minutes (last, max., min., and 10 extra measurements) | | | |
| Detection | Laser diode / contact | | | |
| Update Time | 1 second (typical) | | | |
| Power Requirement | 2 AA 1.5V batteries (Life: Approx. 25 hrs.) | | | |
| Operating Temperature | 32 - 113 °F (0 - 45 °C) | | | |
| Construction | Die-cast aluminum housing | | | |
| Weight | 0.8 lb (365 g) | | | |
| Agency Approvals | CE | | | |
| Dimensions | 6.6 in. L x 2.4 in. W x 1.8 in. H (167.5 mm x 60 mm x 46 mm) | | | |
| בוווכווסוטווס | With contact adapter: Length = 8.25 in. (209 mm) | | | |



Accessories

| DT-200LR Series Accessories | | | | |
|-----------------------------|---|-------|--|--|
| Part Number | Description | Price | | |
| DT-CONE | Replacement standard cone adapter for Shimpo DT series handheld tachometers, 1/2 inch diameter | | | |
| DT-ADP-200LR | Replacement contact adapter for Shimpo DT-205LR or DT-207LR handheld tachometers | | | |
| EXT-SHAFT | Replacement extension shaft for Shimpo DT series handheld tachometers, 3-1/2 inch length | | | |
| DT-FPM-6 | Replacement measuring wheel for Shimpo DT series tachometers, 6 inch circumference | | | |
| DT-FPM-12 | Measuring wheel for Shimpo DT series handheld tachometers, 12 inch circumference | | | |
| DT-FUNNEL | Replacement standard funnel adapter for Shimpo DT series tachometers, 1/2 inch diameter | | | |
| DT-TAB | Reflective tabs, sheet of (35) 1/2-inch squares, for use with Shimpo DT-205LR, DT-207LR and PT-110 handheld tachometers | | | |
| DT-TAPE | Replacement reflective tape strip, 1 x 7-3/4 inch, for use with Shimpo DT-205LR, DT-207LR and PT-110 handheld tachometers | | | |



DT-FUNNEL





Ε

DT-ADP-200LR



DT-FPM-12



DT-TAB



