

# Fuji Duo Series SC-E Contactors

## Features


- 5 to 100 hp at 480 VAC
- cULus and CSA approval, CE mark, meets JIS and IEC standards.
- Models SC-E02-xxx to SC-E4-xxx have 3-pole main circuits and come in three sizes with widths of 43mm, 54mm, and 67mm.
- Models SC-E1-xxx to SC-E7-xxx employ a box terminal structure; allowing wires to be connected directly to the main circuit.
- Has a finger-protection terminal structure that prevents the exposure of live parts.
- Models SC-E5-xxx to SC-E7-xxx use a SUPERMAGNETTM (AC-input/DC-output operation) for high operating reliability and requires no surge suppressor.

## Small Size

- SC-E02-xxx to E05-xxx: 43mm wide
- SC-E1-xxx to E2S-xxx: 54mm wide
- SC-E3-xxx, E4-xxx: 67mm wide
- SC-E5-xxx: 88mm wide



SC-E2S



SC-E7

## Safety

- Terminals with finger-touch protection (DIN 57106/VDE 0106 Teil100)

## Utility

- Box lug terminal construction
- Long electrical life
- Easy to wire

## Environmental

- Low power consumption
- Recycled thermoplastic resin used for plastic parts.
- The names of materials are indicated on all major parts to facilitate recycling

## Standards & Approvals

- UL listed, file E42419, Standard UL 508
- cUL listed, file E42419, Standard CSA C 22.2 No.14
- VDE 0660
- JIS C 8201-4-1
- IEC 60947-4-1 / EN 60947-4-1
- CE compliant

## Optional accessories

- Auxiliary contact blocks
- Coil surge suppression units

## SC-E Series Contactors Specifications - UL and CSA

Part Number	Price	Nominal Coil Voltage	Rated Capacity (HP)						Rated AC-3 Current (A) [note 1]	Rated AC-1 Thermal Current (A) [note 2]	SCCR Ratings (KA)	Rated Insulation Voltage (V)	Frame Width (mm)
			3-Phase Motor				1-Phase Motor						
			200V	220 to 240V	440 to 480V	550 to 600V	100 to 120V	220 to 240V					
<a href="#">SC-E02P-24VAC</a>		24 VAC	2	2	5	5	1/3	1	9	20			
<a href="#">SC-E02P-110VAC</a>		110 VAC											
<a href="#">SC-E02P-220VAC</a>		220 VAC											
<a href="#">SC-E02P-440VAC</a>		440-480 VAC											
<a href="#">SC-E02P-500VAC</a>		500-550 VAC											
<a href="#">SC-E02PG-24VDC</a>		24 VDC	3	3	7.5	7.5	1/2	2	12	20			
<a href="#">SC-E03P-24VAC</a>		24 VAC											
<a href="#">SC-E03P-110VAC</a>		110 VAC											
<a href="#">SC-E03P-220VAC</a>		220 VAC											
<a href="#">SC-E03P-440VAC</a>		440-480 VAC											
<a href="#">SC-E03PG-24VDC</a>		24 VDC	5	5	10	10	1	3	18	25	5	690	43
<a href="#">SC-E04P-24VAC</a>		24 VAC											
<a href="#">SC-E04P-110VAC</a>		110 VAC											
<a href="#">SC-E04P-220VAC</a>		220 VAC											
<a href="#">SC-E04P-440VAC</a>		440-480 VAC											
<a href="#">SC-E04P-500VAC</a>		500-550 VAC											
<a href="#">SC-E04PG-24VDC</a>		24 VDC	5	7.5	15	15	2	3	25	32			
<a href="#">SC-E05P-24VAC</a>		24 VAC											
<a href="#">SC-E05P-110VAC</a>		110 VAC											
<a href="#">SC-E05P-220VAC</a>		220 VAC											
<a href="#">SC-E05P-440VAC</a>		440-480 VAC											
<a href="#">SC-E05P-500VAC</a>		500-550 VAC											
<a href="#">SC-E05PG-24VDC</a>		24 VDC											

TABLE CONTINUED NEXT PAGE

- Notes: 1. AC3 type loads consist of squirrel cage three-phase motors; occasional, limited jogging duty.  
 2. AC1 non-inductive or slightly inductive loads. Typically resistive loads (i.e. furnaces, ovens, etc.)

# Fuji Duo Series SC-E Contactors



SC-E Series Contactors Specifications - UL and CSA													
Model	Price	Nominal Coil Voltage	Rated Capacity (HP)						Rated AC-3 Current (A) [note 1]	Rated AC-1 Thermal Current (A) [note 2]	SCCR Ratings (KA)	Rated Insulation Voltage (V)	Frame Width (mm)
			3-Phase Motor				1-Phase Motor						
			200V	220-240V	440-480V	550-600V	100-20V	220-240V					
<a href="#">SC-E1-24VAC</a>		24 VAC	7.5	10	25	25	2	3	32	50	690	54	
<a href="#">SC-E1-110VAC</a>		110 VAC											
<a href="#">SC-E1-220VAC</a>		220 VAC											
<a href="#">SC-E1-440VAC</a>		440-480 VAC											
<a href="#">SC-E1-500VAC</a>		500-550 VAC											
<a href="#">SC-E1G-24VDC</a>		24 VDC											
<a href="#">SC-E2-24VAC</a>		24 VAC	10	15	30	30	3	5	40	60			
<a href="#">SC-E2-110VAC</a>		110 VAC											
<a href="#">SC-E2-220VAC</a>		220 VAC											
<a href="#">SC-E2-440VAC</a>		440-480 VAC											
<a href="#">SC-E2G-24VDC</a>		24 VDC											
<a href="#">SC-E2S-24VAC</a>		24 VAC	15	20	30	30	3	10	50	65			
<a href="#">SC-E2S-110VAC</a>		110 VAC											
<a href="#">SC-E2S-220VAC</a>		220 VAC											
<a href="#">SC-E2S-440VAC</a>		440-480 VAC											
<a href="#">SC-E2S-500VAC</a>		500-550 VAC											
<a href="#">SC-E2SG-24VDC</a>		24 VDC											
<a href="#">SC-E3-24VAC</a>		24 VAC	20	25	50	50	5	15	65	100			
<a href="#">SC-E3-110VAC</a>		110 VAC											
<a href="#">SC-E3-220VAC</a>		220 VAC											
<a href="#">SC-E3-440VAC</a>		440-480 VAC											
<a href="#">SC-E3G-24VDC</a>		24 VDC											
<a href="#">SC-E4-24VAC</a>		24 VAC	25	30	50	50	5	15	80	105			
<a href="#">SC-E4-110VAC</a>		110 VAC											
<a href="#">SC-E4-220VAC</a>		220 VAC											
<a href="#">SC-E4-440VAC</a>		440-480 VAC											
<a href="#">SC-E4-500VAC</a>		500-550 VAC											
<a href="#">SC-E4G-24VDC</a>		24 VDC											
<a href="#">SC-E5-24V</a>		24 VAC/ VDC	30	30	60	75	7.5	15	105	150			
<a href="#">SC-E5-100V</a>		110 VAC/ VDC											
<a href="#">SC-E5-200V</a>		220 VAC/ VDC											
<a href="#">SC-E5-400V</a>		380-450 VAC											
<a href="#">SC-E5-500V</a>		460-575 VAC											
<a href="#">SC-E6-24V</a>		24 VAC/ VDC	40	40	75	100	10	20	125	150			
<a href="#">SC-E6-100V</a>		110 VAC/ VDC											
<a href="#">SC-E6-200V</a>		220 VAC/ VDC											
<a href="#">SC-E6-500V</a>		460-575 VAC											
<a href="#">SC-E7-24V</a>		24 VAC/ VDC	50	50	100	125	15	25	150	200			
<a href="#">SC-E7-100V</a>		110 VAC/ VDC											
<a href="#">SC-E7-200V</a>		220 VAC/ VDC											
<a href="#">SC-E7-400V</a>		380-450 VAC											
<a href="#">SC-E7-500V</a>		460-575 VAC											

Notes: 1. AC3 type loads consist of squirrel cage three-phase motors; occasional, limited jogging duty.  
 2. AC1 non-inductive or slightly inductive loads. Typically resistive loads (i.e. furnaces, ovens, etc.)

# Fuji Duo Series SC-E Contactors



SC-E Series Contactors Specifications - IEC												
Contactor Type	Rated Capacity (kW)				Rated Operating Current (A)						Rated Thermal Current (A)	Internal Auxilliary Contact Arrangement
	3-Phase Motor AC-3 / AC-4				3-Phase Motor AC-3 / AC-4			Resistive Load AC-1				
	200-240V	380-440V	500-550V	600-690V	200-240V	380-440V	500-550V	600-690V	200-240V	380-440V		
SC-E02(G)-xxx	2.2 / 2.2	4 / 4	4 / NA	4 / NA	9 / 9	9 / 9	7 / NA	5 / NA	20	20	20	-
SC-E03(G)-xxx	3 / 3	5.5 / 5.5	5.5 / NA	5.5 / NA	12 / 12	12 / 12	9 / NA	7 / NA	20	20	20	-
SC-E04(G)-xxx	4 / 4	7.5 / 7.5	7.5 / NA	7.5 / NA	18 / 18	18 / 18	13 / NA	9 / NA	25	25	25	-
SC-E05(G)-xxx	5.5 / 4	11 / 7.5	11 / NA	7.5 / NA	25 / 18	25 / 18	17 / NA	9 / NA	32	32	32	-
SC-E1(G)-xxx	7.5 / 7.5	15 / 15	15 / NA	11 / NA	32 / 32	32 / 32	24 / NA	15 / NA	50	50	50	-
SC-E2(G)-xxx	11 / 11	18.5 / 18.5	18.5 / NA	15 / NA	40 / 40	40 / 40	29 / NA	19 / NA	60	60	60	-
SC-E2S(G)-xxx	15 / 11	22 / 18.5	25 / NA	22 / NA	50 / 40	50 / 40	38 / NA	26 / NA	65	65	65	-
SC-E3(G)-xxx	18.5 / 18.5	30 / 30	37 / NA	30 / NA	68 / 68	65 / 65	60 / NA	38 / NA	100	100	100	-
SC-E4(G)-xxx	22 / 18.5	40 / 30	37 / NA	37 / NA	80 / 68	80 / 65	60 / NA	44 / NA	105	105	105	-
SC-E5-xxx	30 / 30	55 / 55	55 / NA	55 / NA	105 / 105	105 / 105	85 / NA	64 / NA	150	150	150	2 N.O.+2 N.C.
SC-E6-xxx	37 / 37	60 / 60	60 / NA	60 / NA	125 / 125	125 / 125	90 / NA	72 / NA	150	150	150	2 N.O.+2 N.C.
SC-E7-xxx	45 / 45	75 / 75	75 / NA	90 / NA	150 / 150	150 / 150	120 / NA	103 / NA	200	200	200	2 N.O.+2 N.C.

## Internal Auxiliary Contact Ratings

Internal Auxiliary Contact Ratings - UL and CSA						
Frame Size (note 1)	Rated Insulation Voltage (V)	NEMA ICS 5-2000 Ratings (note 2)				
		AC Ratings			DC Ratings	
		Designation	Making VA	Breaking VA	Designation	Making/Breaking VA
E5 to E7-xxx	690	A600	7200	720	Q300	69

### Notes:

- E02(G) to E4(G) do not have internal auxiliary contact.
- NEMA ICS 5-2000. For more information, refer to Control Circuit Contact Electrical Ratings, see page tMRC-130.

Internal Auxiliary Contact Ratings - IEC, JIS									
Based on IEC 60974-4-1, EN 60947-4-1, JIS C 8201-4-1									
Frame Size (note 1)	Rated Insulation Voltage (V)	Rated Thermal Current (A)	Making and Breaking Capacity (A)		Rated Operational Current (A)				Minimum Operating Voltage and Current
			AC Voltage	Amps	AC Voltage	AC-15 (Ind. load)	DC Voltage	DC-13 (Ind. load)	
E5 to E7-xxx	690	10	120V	60	120V	6	24V	3	5 VDC, 3 mA
			220V	30	220V	3	48V	1.5	
			440V	15	440V	1.5	110V	0.55	
			600V	12	600V	1.2	220V	0.27	

Note 1: E02(G) to E4(G) do not have internal auxiliary contact.

# Fuji Duo Series SC-E Contactors

## Coil Characteristics

AC Coil Characteristics								
Frame Size	Power Consumption (VA)		Power Loss (W)		Pick-Up Voltage (V)	Drop-Out Voltage (V)	Operating Time (ms)	
	Inrush	Sealed	50 Hz	60 Hz			Coil ON to Contact ON	Coil OFF to Contact OFF
	50/60 Hz	50/60 Hz						
E02 to E05-xxx	90/95	9/9	2.7	2.8	0.85 - 1.1 x U.S. rated coil voltage	0.2 - 0.75 x U.S. rated coil voltage	9-20	5-16
E1 to E2S-xxx	120/135	12.7/12.4	3.6	3.8	0.85 - 1.1 x U.S. rated coil voltage	0.2 - 0.75 x U.S. rated coil voltage	10-17	6-13
E3, E4-xxx	180/190	13.3/13.4	4.5	5	0.85 - 1.1 x U.S. rated coil voltage	0.2 - 0.75 x U.S. rated coil voltage	10-18	8-18
E5-xxx	80/95	4/4.6	3.2	3.6	0.85 - 1.1 x U.S. rated coil voltage	0.2 - 0.75 x U.S. rated coil voltage	39-45	27-33
E6, E7-xxx	190/230	4.9/5.8	3.4	3.7	0.8 - 1.1 x U.S. rated coil voltage	0.1 - 0.65 x U.S. rated coil voltage	31-37	30-36

DC Coil Characteristics						
Frame Size	Power Consumption (W)		Pick-Up Voltage (V)	Drop-Out Voltage (V)	Operating Time (ms)	
	Inrush	Sealed			Coil ON to Contact ON	Coil OFF to Contact OFF
E02G to E05G-xxx	7	7	0.85 - 1.1 x U.S. rated coil voltage	0.1 - 0.75 x U.S. rated coil voltage	45-49	10-26
E1G to E2SG-xxx	9	9	0.85 - 1.1 x U.S. rated coil voltage	0.1 - 0.75 x U.S. rated coil voltage	40-50	8-17
E3G, E4G-xxx	12	12	0.85 - 1.1 x U.S. rated coil voltage	0.1 - 0.75 x U.S. rated coil voltage	60-70	14-21
E5-xxx	90	2.8	0.85 - 1.1 x U.S. rated coil voltage	0.1 - 0.75 x U.S. rated coil voltage	35-41	26-32
E6, E7-xxx	225	3.2	0.8 - 1.1 x U.S. rated coil voltage	0.1 - 0.65 x U.S. rated coil voltage	28-34	27-33

Operating Coil	
AC Coil, SC-E02-xxx to SC-E4-xxx	
Voltage Code	Coil Operating Voltage / Frequency
24VAC	24 VAC 50 Hz / 24-26 VAC 60 Hz
110VAC	100-110 VAC 50 Hz / 110-120 VAC 60 Hz
220VAC	200-220 VAC 50 Hz / 220-240 VAC 60 Hz
440VAC	415-440 VAC 50 Hz / 440-480 VAC 60 Hz
500VAC	480-500 VAC 50 Hz / 500-550 VAC 60 Hz

Operating Coil	
AC/DC Coil (SUPERMAGNET), SC-E5-xxx to SC-E7-xxx	
Voltage Code	Coil Operating Voltage/Frequency
24V	24-25 VAC 50/60 Hz; 24 VDC
100V	100-127 VAC 50/60 Hz; 100-120 VDC
200V	200-250 VAC 50/60 Hz; 200-240 VDC
400V	380-450 VAC 50/60 Hz
500V	460-575 VAC 50/60 Hz

Operating Coil	
DC Coil, SC-E02G-xxx to SC-E4G-xxx	
Voltage Code	Coil Operating Voltage
24VDC	24 VDC

## Performance Data


Frame size	Making current (A)		Breaking current (A)		Operating cycles per hour	Durability (operations)	
	220V	440V	220V	440V		Electrical	Mechanical
SC-E02	108	108	90	90	1800	2 million	10 million
SC-E03	144	144	120	120	1800	1.5 million	10 million
SC-E04	216	216	180	180	1800	1.5 million	10 million
SC-E05	250	250	200	200	1200	1.5 million	10 million
SC-E1	384	384	320	320	1200	1.5 million	10 million
SC-E2	480	480	400	400	1200	1.5 million	10 million
SC-E2S	500	500	400	400	1200	1.5 million	10 million
SC-E3	816	780	680	650	1200	1.5 million	5 million
SC-E4	816	800	680	650	1200	1 million	5 million
SC-E5	1260	1260	1050	1050	1200	1 million	5 million
SC-E6	1500	1500	1250	1250	1200	1 million	5 million
SC-E7	1800	1800	1500	1500	1200	1 million	5 million


# Fuji Duo Series SC-E Contactors



## Standard operating conditions

The magnetic contactors are manufactured for use in the standard operating conditions given in the table.




Standard Operating Conditions	
<b>Ambient Temperature</b>	Operating: -5 to +55 °C [+23 to +131 °F] No sudden temperature changes resulting in condensation or icing (The average temperature over a 24-hour period must not exceed 35 °C [95 °F]) Storage: -40 to +65 °C [-40 to +149 °F]
<b>Humidity</b>	45 to 85% RH
<b>Altitude</b>	2000m or lower
<b>Atmosphere</b>	No excessive dust, smoke, corrosive gases, flammable gases, steam, or salt
<b>Vibration</b>	10 to 55 Hz 15 m/s <sup>2</sup>
<b>Shock</b>	50 m/s <sup>2</sup>
<b>Mounting</b>	35mm IEC DIN rail mounting (SC-E02 to SC-E4), screw mounting
<b>Mounting Angle</b>	
<b>Standard</b>	IEC 947-4-1, EN 60947-4-1, VDE 0660 JIS C 8201-4-1, JEM 1038 UL 508, file E42419; CSA C22.2, file 20479


## Wiring

Be sure to perform wiring correctly with reference to the wiring diagrams. Main terminals for models SC-E02 to SC-E7 are wired using solid wires or stranded wires. Stranded wires or flexible stranded wires can be connected by twisting them together and crimping a sleeve (ferrule) onto them before connecting.

## Tightening torque

If wires are not tightened sufficiently, they may become hot or loosen, resulting in a fire, short-circuit, electric shock, or other potentially dangerous situation. Tighten wires to the torques specified in these tables.

Wire Sizes, Tightening Torques - Control Circuit		
<b>Solid or Stranded Wire (mm<sup>2</sup>)</b>	<b>One</b>	0.75 to 2.5 (1 to 1.6mm diameter)
	<b>Two</b>	0.75 to 2.5 (1 to 1.6mm diameter)
<b>Stranded Wire Flexible Stranded Wire</b>	<b>mm [in]</b>	0.75 to 2.5 [0.03 to 0.10]
	<b>AWG</b>	18 to 14
<b>Ring Terminal [SC-E0x(P) only]</b>	<b>mm [in]</b>	7.7 [0.30]
<b>AWG</b>	<b>One</b>	18 to 14
	<b>Two</b>	18 to 14
<b>Insulation Stripping Length</b>		
<b>Fork Terminal</b>	Max. 7.7mm wide	
<b>Terminal Screw Size</b>	M3.5	
<b>Tool</b>	Phillips screwdriver, H-type, No. 2 (ISO 8764); ADC part number TW-SD-VPH-1 or TW-SD-VPH-2 Flat-blade screwdriver, 1 x 5.5 x L-type, B (ISO 2830); ADC part number TW-SD-VSL-4	
<b>Tightening Torque (N.m)</b>	0.8 to 1	

Wire Sizes, Tightening Torques - Main Circuit					
Contactor Type		SC-E02-xxx	SC-E03-xxx	SC-E04-xxx	SC-E05-xxx
<b>Solid Wire (mm<sup>2</sup>)</b>	<b>One</b>	0.75 to 4		0.75 to 6	
	<b>Two</b>	1 to 4		1.5 to 6	
<b>Stranded Wire Flexible Stranded Wire</b>	<b>mm [in]</b>	0.75 to 10 [0.03 to 0.39]			
	<b>AWG</b>	18 to 8			
<b>Ring Terminal [SC-E0x(P) only]</b>	<b>mm [in]</b>	Maximum 9.7mm [0.38in] wide			
<b>AWG</b>	<b>One</b>	12 maximum		10 maximum	
	<b>Two</b>	12 maximum		10 maximum	
<b>Insulation Stripping Length</b>					
<b>Terminal Screw Size</b>	M4				
<b>Tool</b>	Phillips screwdriver, H-type, No. 2 (ISO 8764); ADC part number TW-SD-VPH-1 or TW-SD-VPH-2 Flat-blade screwdriver, 1 x 5.5 x L-type, B (ISO 2830); ADC part number TW-SD-VSL-4				
<b>Tightening Torque (N.m)</b>	1.2 to 1.5				

# Fuji Duo Series SC-E Contactors

Wire Sizes, Tightening Torques - Main Circuit						
Contactor Type		SC-E1, E2, E2S-xxx	SC-E3, E4-xxx	SC-E5, E6-xxx	SC-E7-xxx	
Top-Only Connection	Solid or stranded wire (mm <sup>2</sup> ) <sup>1</sup>		0.75 to 35	1.5 to 70	4 to 70	4 to 120
	Flexible stranded wire with sleeve (mm <sup>2</sup> ) <sup>1</sup>		0.75 to 25	1.5 to 50	2.5 to 50	2.5 to 95
	Flexible stranded wire without sleeve (mm <sup>2</sup> )		0.75 to 25	1.5 to 50	4 to 50	4 to 95
	AWG		18 to 2	16 to 2/0	12 to 2/0	12 to 250 MCM
	Solid or stripping length (mm)		15	19.5	26.5	28.5
Bottom-Only Connection	Single stranded wire (mm <sup>2</sup> ) <sup>1</sup>		0.75 to 25	1.5 to 50	4 to 70	4 to 120
	Flexible stranded wire with sleeve (mm <sup>2</sup> ) <sup>1</sup>		0.75 to 16	1.5 to 35	2.5 to 50	2.5 to 95
	Flexible stranded wire without sleeve (mm <sup>2</sup> )		0.75 to 16	1.5 to 35	4 to 50	4 to 95
	AWG		18 to 3	16 to 1/0	12 to 2/0	12 to 250 MCM
	Sheath stripping length (mm)		12.5	16	26.5	28.5
Top/Bottom Connection	Solid or stranded wire (mm <sup>2</sup> ) <sup>1</sup>	Top/bottom	0.75 to 25	1.5 to 50	4 to 70	4 to 120
	Flexible stranded wire with sleeve (mm <sup>2</sup> ) <sup>1</sup>	Top/bottom	0.75 to 16	1.5 to 35	2.5 to 50	2.5 to 95
	Flexible stranded wire without sleeve (mm <sup>2</sup> )	Top/bottom	0.75 to 16	1.5 to 35	4 to 50	4 to 95
	AWG	Top/bottom	18 to 3	16 to 1/0	12 to 2/0	12 to 250 MCM
Tool			Phillips screwdriver, H-type, No.2 (ISO 8764); ADC part number DN-SP1 or DN-SP2	Hex. wrench 4 (ISO 2936)		
			Flat-blade screwdriver, 1 x 5, 5xL-type, B (ISO 2830); ADC part number DN-SS5			
Tightening Torque (N•m)			2.5	8	10	
Self-locking Torque (N•m) <sup>2</sup>			1	2		

Note 1: Stranded wire (0 to 25 mm<sup>2</sup>) consists of 7 wires or less.  
Stranded wire (35 to 120 mm<sup>2</sup>) consists of 19 wires or less.


Flexible stranded wire consists of more number wires than the above.

Note 2: The tightening bolt must be loosened in order to insert the wire. However, stop loosening the bolt when the anti-drop attachment on the bottom of the bolt reaches the top edge of the terminal. If a torque exceeding that given in the table is applied in this state, the retaining bracket may loosen.


# Fuji Duo Series SC-E Contactors

## Electrical durability


AC-3 duty / SC-E02 to SC-E05-xxx



AC-3 duty / SC-E1 to SC-E7-xxx




AC-1 duty / SC-E02 to SC-E7-xxx



# Fuji Duo Series SC-E Contactors

## Accessories

### Optional accessories



#### Auxiliary contact blocks with terminal covers

Maximum auxiliary contact blocks:

2 side mounted (1 per side) OR 1 front mounted. The front and side blocks cannot be mounted together on the same contactor.



**SZ-A22T**



**SZ-A11T**



**SZ-AS1T**



**SZ-AS2T**

#### Caution on use:

1. Front mounting auxiliary contact block and side mounting block cannot be attached to one contactor at the same time.
2. Only one front mounting block can be attached to one contactor.
3. Where interlock unit is already attached, side mounting auxiliary contact block can be attached on one side only.

Auxiliary Contact Blocks with Terminal Covers					
Part Number	Price	Applicable Contactor	Mounting	Number of Contacts	Contact Arrangement
<a href="#"><u>SZ-A22T</u></a>		SC-E02(G)-xxx to E4(G)-xxx	Front mounting	4	2 N.O.+2 N.C.
<a href="#"><u>SZ-A20T</u></a>				2	2 N.O.
<a href="#"><u>SZ-A11T</u></a>				2	1 N.O. + 1 N.C.
<a href="#"><u>SZ-AS1T</u></a>		SC-E02(G)-xxx to E4(G)-xxx	Side mounting	2	1 N.O. + 1 N.C.
<a href="#"><u>SZ-AS2T</u></a>				2	1 N.O. + 1 N.C.

Accessory Auxiliary Contact Ratings - UL and CSA				
NEMA ICS 5-2000 Ratings ( note 1 )				
AC Ratings			DC Ratings	
Designation	Making VA	Breaking VA	Designation	Making/Breaking VA
<b>A600</b>	7200	720	Q300	69

Note: For more information, refer to Control Circuit Contact Electrical Ratings

Accessory Auxiliary Contact Ratings - IEC and JIS continued on next page.

# Fuji Duo Series SC-E Contactors Accessories

Accessory Auxiliary Contact Ratings - IEC and JIS							
Rated Thermal Current (A)	Making and Breaking Capacity at AC (A)		Rated operational current (A)				Minimum Operating Voltage and Current
			AC		DC		
			Voltage	AC-15 (Ind. load)	Voltage	DC-13 (Ind. load)	
10	120V	60	120V	6	24V	3	5 VDC, 3 mA
	220V	30	220V	3	48V	1.5	
	440V	15	440V	1.5	110V	0.55	
	600V	12	600V	1.2	220V	0.27	

### Coil surge suppression units



**SZ-Z1**




**SZ-Z37**

Suppress surge voltage due to contactor ON-OFF operations; easily connect to contactor coil terminals.

*Important: When driving 24 VDC Fuji contactors with a PLC solid-state output, we recommend using diode terminal block part number DN-D10DR-A or ZL-TSD8-24. Please see application note AN-MISC-032 for additional information located on [AutomationDirect.com/technotes](http://AutomationDirect.com/technotes).*

Coil Surge Suppression Units					
Part Number	Price	Applicable Contactor		Operating Coil Voltage	Device
		AC Operated	DC Operated		
<b>SZ-Z1</b>		SC-E02-xxx to E05-xxx	SC-E02G-xxx to E05G-xxx	24-48 VAC/VDC	varistor
<b>SZ-Z2</b>				100-250 VAC/VDC	
<b>SZ-Z31</b>		SC-E1-xxx to -E4xxx	SC-E1G-xxx to E4G-xxx	24-48 VAC/VDC	capacitor / resistor
<b>SZ-Z32</b>				100-250 VAC/VDC	
<b>SZ-Z4</b>		SC-E02-xxx to E05-xxx	SC-E02G-xxx to E05G-xxx	24-48 VAC/VDC	capacitor / resistor
<b>SZ-Z5</b>				100-250 VAC/VDC	
<b>SZ-Z34</b>		SC-E1-xxx to E4-xxx	-	24-48 VAC/VDC	capacitor / resistor
<b>SZ-Z35</b>				100-250 VAC/VDC	
<b>SZ-Z36</b>				24-48 VAC/VDC	
<b>SZ-Z37</b>			SC-E1G-xxx to E4G-xxx	100-250 VAC/VDC	
<b>SC-E02 to E05</b>				380-440 VAC/VDC	
<b>SC-E1 to E4</b>				380-440 VAC/VDC	

*Note: Super Magnet Coils on SC-E5, SC-E6, and SC-E7 contactors have internal surge suppression. See diagram below.*



# Fuji Duo Series SC-E Accessories

## Connection kits for reversing SC-E contactors




**SZ-ERW1A**



**SZ-ERW1B**




**SZ-ERW1D**



**SZ-ERW2A**



**SZ-ERW2B**



**SZ-ERW2D**




**SZ-ERW3A**



**SZ-ERW3B**



**SZ-ERW3D**



Connection Kits			
Part Number	Price	Description	Use with Contactors
<a href="#">SZ-ERW1A</a>		Line side reversing connection kit.	SC-E02-xxx to SC-E05-xxx
<a href="#">SZ-ERW1B*</a>		Load side reversing connection kit. For wiring load side when using contactors only or with a MMS device.	
<a href="#">SZ-ERW1D</a>		Load side reversing connection kit. For wiring load side when using two contactors with a thermal overload relay.	
<a href="#">SZ-ERW2A</a>		Line side reversing connection kit.	SC-E1-xxx to SC-E2S-xxx
<a href="#">SZ-ERW2B*</a>		Load side reversing connection kit. For wiring load side when using contactors only or with a MMS device.	
<a href="#">SZ-ERW2D</a>		Load side reversing connection kit. For wiring load side when using two contactors with a thermal overload relay.	
<a href="#">SZ-ERW3A</a>		Line side reversing connection kit.	SC-E3-xxx to SC-E4-xxx
<a href="#">SZ-ERW3B*</a>		Load side reversing connection kit. For wiring load side when using contactors only or with a MMS device.	
<a href="#">SZ-ERW3D</a>		Load side reversing connection kit. For wiring load side when using two contactors with a thermal overload relay.	

\* When using the SZ-ERWxB, a TK-E thermal overload relay must be separately mounted and wired using an SZ-HxE base. To assemble a TK-E overload directly to the contactor use a SZ-ERWxD load side connection kit.

## Mechanical interlock unit



**SZ-RM**

Mechanical Interlock Unit			
Part Number	Price	Description	Use with Contactors
<a href="#">SZ-RM</a>		Used when building a reversing starter. Prevents both contactors from being pulled in at once.	SC-E02-xxx to SC-E4-xxx

NOTE: Mechanical interlock unit cannot be used with SC-E5-xxx through E7-xxx contactors.

## Parts for reversing Fuji SC-E contactors

- SC-E (Contactors - qty. 2)
- SZ-ERWxA (Line side connection kit - qty. 1)
- SZ-ERWxB\* (Load side connection kit - qty. 1)
- SZ-RM (Mechanical interlock - qty. 1)
- SZ-AxxT (Auxiliary contact blocks - qty. 1)




# Fuji Duo Series SC-E Contactors

## Dimensions (mm)

### Contactors


SC-E02,E03,E04,E05-xxx



Weight: 0.33 kg

Use the mounting holes on a diagonal line  
 ① ② to mount contactor  
 ① 35X 6②:35X (48 to) 52


SC-E1,E2,E2S-xxx



Weight: 0.58 kg

Use the mounting holes on a diagonal line  
 ① ② to mount contactor  
 ① 45X 75②:45 (38 to) 46 80

SC-E3,E4-xxx




Weight: 1.1 kg

Use the mounting holes on a diagonal line  
 ① ② to mount contactor  
 ① 55(to) X60 ②(54 to)X60 90

## Wiring diagrams


### Contactors

SC-E02 to E05-xxx  
 SC-E1 to E4-xxx  
 SC-E02G to E05G-xxx  
 SC-E1G to E4G-xxx  
 SC-E2S, E2SG-xxx



\*1 In case of aux. contact 2NO+

SC-E5,E6,E7-xxx




\*1 In case of aux. contact 4NO+

# Fuji Duo Series SC-E Contactors



## Dimensions (mm)

### Contactors

SC-E5-xxx




Weight: 2.0 kg





\*1 Side mounting contactor  
\*2 Front mounting contactor




SC-E6-xxx





Weight: 2.6 kg




SC-E7-xxx





Weight: 2.9 kg



SC-E02G,E03G,E04G,E05G-xxx



Weight: 0.59 kg




Use the  $\phi$  mounting holes on a diagonal line  
 ① ② to mount contactor  
 ① 35× ② 35× (48 to) 52

# Fuji Duo Series SC-E Contactors


## Dimensions [mm]

### Contactors


SC-E1G,E2G,E2SG-xxx



Weight: 0.79 kg




Panel drilling




\*1 Side mounting contactor  
\*2 Front mounting contactor

Use the mounting holes on a diagonal  
① ② to mount contactor  
① 45× 75②:45 (38 to 46) 80


SC-E3G,E4G-xxx



Weight: 1.4 kg



Panel drilling




\*1 Side mounting contactor  
\*2 Front mounting contactor

Use the mounting holes on a diagonal  
① ② to mount contactor  
① 55 (to) 80 ②: (54 to) 80 90

## Dimensions [mm]

### Auxiliary contact blocks - front mounting

SZ-A22T, A20T, A11T for SC-E02 (G)-xxx to E4 (G)-xxx






A22T Weight: 36 g  
SZ-A20T,A11T Weight: 20 g

Type	A	B	C
SC-E02, E03, E04, E05-xxx	43	80	109
SC-E1, E2, E2S-xxx	54	90	124
SC-E3, E4-xxx	67	112	139
SC-E02G, E03G, E04G, E05(G)-xxx	43	80	136
SC-E1G, E2G, E2SG-xxx	54	90	149.5
SC-E3G, E4G-xxx	67	112	158

## Wiring Diagrams

SZ-A22T, A20T, A11T



# Fuji Duo Series SC-E Contactors


## Dimensions (mm)

Auxiliary contact blocks - side mounting

## Wiring Diagrams

SZ-AS1T for SC-E02 (G)-xxx to E4 (G)-xxx

Contactor with aux. contact block



Weight: 28 g

Type	A	B	C	D
SC-E02, E03, E04, E05-xxx	67	80	81	43
SC-E1, E2, E2S-xxx	78	90	54	54
SC-E3, E4-xxx	91	112	67	67
SC-E02G, E03G, E04G, E05 (G)-xxx	67	80	108	43
SC-E1G, E2G, E2SG-xxx	78	90	121.5	54
SC-E3G, E4G-xxx	91	112	130	67

1 N.O. + 1 N.C.

Mounted on right




Mounted on left



SZ-AS2T for SC-E5 to E7-xxx

Contactor with aux. contact block



Weight: 40 g

Type	A	B	C	D
SC-E5-xxx	112	155	132	88
SC-E6-xxx	124	168	138	100
SC-E7-xxx	139	175	140	115

1 N.O. + 1 N.C.

Mounted on right



Mounted on left :




# Fuji Duo Series SC-E Contactors

## Dimensions (mm)


Coil surge suppression units

### SZ-Z1, Z2, Z4, Z5




Weight: 14g


### SZ-Z31, Z32, Z34, Z35, Z36, Z36, Z37



Weight: 15g




### SZ-RM




## Wiring Diagrams


SC-E02 to E05-xxx + SZ-Z1,Z2  
(Built-in varistor)



SC-E02 to E05-xxx + SZ-Z4, Z5  
(Built-in capacitor/resistor)



SC-E1 to E4-xxx + SZ-Z31,Z32  
(Built-in varistor)



SC-E1 to E4-xxx + SZ-Z34, Z35  
(Built-in capacitor/resistor)

SC-E1G to E4G-xxx + SZ-Z36, Z37  
(Built-in capacitor/resistor)

