

# Contrinex Safety Light Curtains Accessories

Safety Light Curtains Accessories Overview			
Part Number	Price	Description	Use With
<b>Mirror Columns</b>			
<b><u>YXC-1060-M11</u></b>	\$692.00	Safety light curtain mirror column. 1060mm housing height, 974mm mirror length, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included.	YBB-xxxx-0150-xxx to YBB-xxxx-0800-xxx units
<b><u>YXC-1660-M11</u></b>	\$946.00	Safety light curtain mirror column. 1660mm housing height, 1574mm mirror length, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included.	YBB-xxxx-1200-xxx to YBB-xxxx-1400-xxxx units YCA-xxxx-4400-xxx units
<b><u>YXC-1960-M11</u></b>	\$1,076.00	Safety light curtain mirror column. 1960mm housing height, 1874mm mirror length, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included.	YBB-xxxx-1600-xxx to YBB-xxxx-1700-xxxx units
<b><u>YXC-1360-M23</u></b>	\$422.00	Safety light curtain mirror column. 1360mm housing height, 2 x 400 beam gap, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included.	YCA-xxxx-3400-xxx units
<b><u>YXC-1360-M24</u></b>	\$504.00	Safety light curtain mirror column. 1360mm housing height, 3 x 300 beam gap, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included.	YCA-xxxx-4300-xxx units
<b>Protective Columns</b>			
<b><u>YXC-1960-F00</u></b>	\$487.00	Safety light curtain protective column. 1897mm housing height, aluminum profile with steel floor plates. Powder-varnished yellow (RAL1021) finish. Mounting hardware included. Two required to protect sender and receiver. 1/pk.	YBB-xxxx-1600-xxx to YBB-xxxx-1800-xxxx units
<b>Other</b>			
<b><u>YXL-0001-000</u></b>	\$259.00	Laser alignment tool for safety light curtains, class 2 laser, range up to 50 meters, useable and clippable to YBB and YCA light curtains models, 2 AAA batteries included.	YBB Series YCA Series
<b><u>YXW-0001-000</u></b>	\$6.75	Safety light curtain mounting brackets for top and bottom mounting. Plastic. 2/pk.	
<b><u>YXW-0003-000</u></b>	\$6.75	Safety light curtain sliding T-nuts for side mounting. Metal. 2/pk. Ideal torque from M5x0.8 thread is 6 Nm (4.42 lb-ft, 53.1 lb-in.).	



### Light Curtain Mirror Columns

- Multi-sided safe guarding of danger zones
- Robust protective profile
- 10% reduction of operating distance for mirror



### Light Curtain Protective Column

- Automatically bounces back after physical shock or vibration.
- Robust baseplate allows radial and vertical alignment.
- Solid aluminum profile



**YXW-0001-000**



**YXW-0003-000**




**YXL-0001-000**

# Contrinex Safety Light Curtains Accessories

## Dimensions mm [in]


### Protective column



### Mirror column

CONTINUOUS MIRROR

SEGMENTED MIRRORS




Safety Light Curtains Protective Columns Dimensions		
Part Number	Total Height A mm [in]	Housing Height B mm [in]
<b>YXC-1960-F00</b>	1960 [77.17]	1897 [74.69]


Safety Light Curtains Mirror Columns Dimensions				
Part Number	Total Height A mm [in]	Mirror Height B mm [in]	Height to Lowest Beam C mm [in]	Beam Gap D mm [in]
<b>YXC-1060-M11</b>	1060 [41.73]	974 [38.35]	n/a	n/a
<b>YXC-1360-M11</b>	1360 [53.54]	1274 [50.16]	n/a	n/a
<b>YXC-1660-M11</b>	1660 [65.35]	1574 [61.97]	n/a	n/a
<b>YXC-1960-M11</b>	1960 [77.17]	1874 [73.78]	n/a	n/a
<b>YXC-1360-M23</b>	1360 [53.54]	n/a	2 x 400 [2 x 15.75]	300 [11.81]
<b>YXC-1360-M24</b>	1360 [53.54]	n/a	3 x 300 [2 x 11.81]	300 [11.81]

Note: Full and open top caps are provided to accommodate taller units.

### Mounting bracket



### T-Nuts for side mounting




# Contrinex Safety Light Curtains Accessories

## Mounting bracket




**YXW-0001-000**



## T-Nuts for side mounting



**YXW-0003-000**



## Laser Alignment Tool


- Clips on YBB and YCA Curtains/Barriers
- High quality lens for narrow output beam
- Up to 50m [164ft] range
- <1mW output power
- Standard AA batteries included



**YXL-0001-000**

Laser Alignment Tool YXL-0001-000 Specifications	
Supply Voltage Range	2.5 – 3.3 VDC
Laser Module Optical Output Power	<1mW (Class 2)
Range	50m (164ft)
Ambient Temperature Range	0-40°C (32-104°F)
Storage Temperature Range	0-60°C (32-140°F)
Wavelength	655nm ± 1%
Laser Beam Spot Size at 10m	< 10mm
Divergence Angle	1.1 mrad
Housing Material	PA with 30% fiberglass
Mounting	Clippable onto YBB / YCA devices
Weight	95g (0.21 lb)

## Dimensions mm [in]



See our website [www.AutomationDirect.com](http://www.AutomationDirect.com) for complete engineering drawings.

**Warning: Safety products sold by AutomationDirect are Safety components only.**

The purchaser/installer is solely responsible for the application of these components and ensuring all necessary steps have been taken to assure each application and use meets all performance and applicable safety requirements and/or local, national and/or international safety codes as required by the application. AutomationDirect cannot certify that our products used solely or in conjunction with other AutomationDirect or other vendors' products will assure safety for any application.

Any person using or applying any products sold by AutomationDirect is responsible for learning the safety requirements for their individual application and applying them, and therefore assumes all risks, and accepts full and complete responsibility for the selection and suitability of the product for their respective application. AutomationDirect does not provide design or consulting services, and cannot advise whether any specific application or use of our products would ensure compliance with the safety requirements for any application.




# Contrinex Safety Light Curtains YBxS Accessories

Contrinex Safety Light Curtains YBxS Accessories					
Part Number	Price	Description	Material	Mounting	Use With
<u><a href="#">YXW-0005-000</a></u>	\$10.00	Contrinex mounting bracket. Package of 2.	Glass fiber reinforced polyamide	Top and bottom mount	YBxS series light curtains
<u><a href="#">YXW-0006-000</a></u>	\$20.00	Contrinex mounting bracket. Package of 2.	Stainless steel	Side mount	YBxS series light curtains
<u><a href="#">YXW-0007-000</a></u>	\$19.00	Contrinex mounting bracket. Package of 2.	Stainless steel	Side or end mount	YBxS series light curtains



[YXW-0005-000](#)



[YXW-0006-000](#)



[YXW-0007-000](#)



**Warning: Safety products sold by AutomationDirect are Safety components only.**

*The purchaser/installer is solely responsible for the application of these components and ensuring all necessary steps have been taken to assure each application and use meets all performance and applicable safety requirements and/or local, national and/or international safety codes as required by the application. AutomationDirect cannot certify that our products used solely or in conjunction with other AutomationDirect or other vendors' products will assure safety for any application.*

*Any person using or applying any products sold by AutomationDirect is responsible for learning the safety requirements for their individual application and applying them, and therefore assumes all risks, and accepts full and complete responsibility for the selection and suitability of the product for their respective application. AutomationDirect does not provide design or consulting services, and cannot advise whether any specific application or use of our products would ensure compliance with the safety requirements for any application.*