Schmersal Two-Hand Control Replacement Pushbuttons





EDRR40RT



EDP55SW

Schmersal Two-Hand Control Replacement Pushbuttons*							
Part Number	EDRR40RT **	EDP55SW					
Price	\$31.50	\$40.50					
Description	Emergency stop pushbutton with mounting flange, push to latch, twist and pull to unlatch, front plate mounting	Momentary pushbutton with mounting flange, front plate mounting					
Front Ring Color	Gold	Silver					
Mounting Diameter	22.3 mm [0.88 in]	22.3 mm [0.88 in]					
Actuating Stroke	5mm [0.20 in]	5mm [0.20 in]					
Dome Material	Anodized aluminum	Anodized aluminum					
Front Ring Material	Anodized aluminum	Anodized aluminum					
Front Panel Thickness	1.5 to 6 mm [0.06 to 0.24 in]	1.5 to 6 mm [0.06 to 0.24 in]					
Weight	91g [3.20 oz]	91g [3.20 oz]					
Mounting Screws Tightening Torque	0.6 N•m [0.44 lb•ft]	0.6 N•m [0.44 lb•ft]					
Ambient Temperature	-25°C to +75°C [-13°F to +167°F]	-25°C to +75°C [-13°F to +167°F]					
Shock Resistance	30g / 18ms	30g / 18ms					
Ingress Protection Rating	IP65	IP65					
Mechanical Life	100,000 operations	1,000,000 operations					
Standards	EN 60947-5-1; EN 60947-1; UL File E57648	EN 60947-5-1; UL File 57648					
Dimensional Drawing	PDF	PDF					


^{*} Operator only. Purchase contact blocks separately.

Dimensions

mm [in]










ISOMETRIC VIEW

EDP55SW



27.5 [1.08] 45.0 [1.77] -[1.8]	ISOMETRIC

Schmersal Legend Plate							
Part Number	ort Number Price Description		Dimensional Drawing				
MDP-8.1	\$4.00 Schmersal legend plate, thermoplastic, round, yellow field, yellow background, blank legend plate.		PDF				



^{**} Part number EFR is required to use this operator

SCHMERSAL Contact Blocks







EF103.2



EF220.2



EF303.2

Contact Blocks								
Part Number	Price	Qty.	Drawing Link	Contacts	Mounting Position	Travel Diagram (mm)	Wiring Diagram	Application
<u>EF10.1</u> *	\$10.00	1	PDF		1			
EF10.2*	\$10.00	1	PDF	1 N.C.	2	0 2 4 6		
<i>EF10.3</i> *	\$10.00	1	PDF		3		•	
EF03.1	\$10.00	1	PDF		1			
EF03.2	\$10.00	1	PDF	1 N.O.	2	0 2 4 6		
EF03.3	\$10.00	1	PDF		3			
<u>EF110.1</u> *	\$15.50	1	PDF		1	0 2 4 6	7/	
EF110.2*	\$16.00	1	PDF	2 N.C.	2		<u>-</u> " !	Standard
EF110.3*	\$16.00	1	PDF		3			
EF033.1	\$16.00	1	PDF		1	0 2 4 6		
EF033.2	\$16.00	1	PDF	2 N.O.	2		_ ;_	
EF033.3	\$16.00	1	PDF		3			
EF103.1*	\$12.50	1	PDF		1	0 2 4 6		
EF103.2*	\$12.50	1	PDF	1 N.C. / 1 N.O.	2		7 i	
EF103.3*	\$12.50	1	PDF		3			
EF220.1**	\$16.00	1	PDF		1	0 2 4 6	7/	
EF220.2**	\$16.00	1	PDF	2 N.C.	2		<u> </u>	
EF220.3**	\$16.00	1	PDF		3		7	Emergency
EF303.1**	\$12.50	1	PDF		1			Stop
EF303.2**	\$12.50	1	PDF	1 N.C. / 1 N.O.	2	0 2 4 6	+7	
EF303.3**	\$12.50	1	PDF		3			

Travel Diagram Legend

= contact closed

= contact open

Numbers indicate distance in mm





www.automationdirect.com

^{*}Not suitable for Emergency Stop devices
**Not suitable for maintained selector switches NWS/NWT

Safety Products



Warning: Safety products sold by AutomationDirect are Safety components only. The purchaser/installer is solely responsible for the application of these components and ensuring all necessary steps have been taken to assure each application and use meets all performance and applicable safety requirements and/or local, national and/or international safety codes as required by the application. AutomationDirect cannot certify that our products, used solely or in conjunction with other AutomationDirect or other vendors' products, will assure safety for any application. Any person using or applying any products sold by AutomationDirect is responsible for learning the safety requirements for their individual application and applying them, and therefore assumes all risks, and accepts full and complete responsibility, for the selection and suitability of the product for their respective application.

AutomationDirect does not provide design or consulting services, and cannot advise whether any specific application or use of our products would ensure compliance with the safety requirements for any application.