

# FlatSIGN Signal Lights

## WERMA FlatSIGN 691 Series

### Features

- Industrial signal light
- Red/Yellow/Green LEDs
- Permanent or blinking (DIP switch selectable)
- 160-degree viewing angle
- Wall mount installation
- Audible alert option with 8
- DIP switch-selectable tones (DC models) or continuous
- (AC models)
- 2-year warranty



FlatSIGN 691 Series Technical Specifications													
Part Number	Price	Drawing Link	Description	Voltage	Housing Color	Current	Operating Temp/Protection	Life Duration	Housing Material	Weight g [oz]	Wiring Diagram	Connection	Agency Approval
<b>Base Mount</b>													
<a href="#">69110055</a>	\$155.00	PDF	Permanent or blinking LED	24V AC/DC	Transparent	30mA per tier	-30 to 50°C (-22 to 122°F) IP65 when mounted	max. 50,000h	PC transparent or coated cap/PC/ABS blend housing	230 [8.11]	Diagram 1	Membrane grommet Cable diameter max. 13mm Terminal screw 0.5 -1.5 mm <sup>2</sup>	UL file E164155, CE, RoH
<a href="#">69130055</a>	\$222.00	PDF			Silver								
<a href="#">69110068</a>	\$155.00	PDF		Transparent									
<a href="#">69130068</a>	\$222.00	PDF		Silver									
<a href="#">69120055</a>	\$188.00	PDF	Permanent or blinking LED Audible alert (8 selectable tones, 80dB at 1 meter)	24V AC/DC	Transparent								
<a href="#">69140055</a>	\$262.00	PDF			Silver								
<a href="#">69120068</a>	\$188.00	PDF	Permanent or blinking LED Audible alert (continuous tone, 80dB at 1 meter)	115-230 VAC	Transparent								
<a href="#">69140068</a>	\$262.00	PDF			Silver								

### Wiring Diagrams

Diagram 1




Diagram 2

