


# Wiring Duct – Accessories

## Duct Separators


Duct separators allow the physical separation of circuits within a single piece of duct. The various mounting arrangements allow alternate compartmentalization of duct and differing ratios of usable sections.

Duct Separators					
Part Number	Price	Description	Color	Pcs/Pkg	Length ft (m)
<b>SEP-15E-1</b>	\$6.00	Separator for 1.5" high duct	Gray	1	6.56 (2)
<b>SEP-22E-1</b>	\$8.00	Separator for 2.25" high duct	Gray	1	6.56 (2)
<b>SEP-30E-1</b>	\$9.00	Separator for 3.0" high duct	Gray	1	6.56 (2)

**Note:** Length of separators is 6.56' (2m).



**SEP-15E**



**SEP-E Mounting Detail**  
Order ZP1 mount separately




**SEP-XXE**

**Note:** Dimensions are in inches (mm).



## Wire Retainers

For holding wires during wiring operations, these retainers are essential. They allow easy access to the interior of the wiring duct during maintenance or alterations, while assuring that wiring bundles will not fall out when the duct cover is removed. Installed with a simple rotating movement, they anchor firmly in the recess boss in the duct base.

Wire Retainers				
Part Number	Price	Description	Color	Pcs/Pkg
<b>CL-1515</b>	\$51.00	Wire retainer fastener for 1.5" x 1.5" duct	Gray	40
<b>CL-1522</b>	\$55.00	Wire retainer fastener for 1.5" x 2.25" duct	Gray	40
<b>CL-1530</b>	\$31.00	Wire retainer fastener for 1.5" x 3.0" duct	Gray	20
<b>CL-2215</b>	\$60.00	Wire retainer fastener for 2.25" x 1.5" duct	Gray	40
<b>CL-2222</b>	\$34.00	Wire retainer fastener for 2.25" x 2.25" duct	Gray	20
<b>CL-2230</b>	\$34.00	Wire retainer fastener for 2.25" x 3.0" duct	Gray	20
<b>CL-2240</b>	\$38.00	Wire retainer fastener for 2.25" x 4.0" duct	Gray	20
<b>CL-3022</b>	\$21.00	Wire retainer fastener for 3.0" x 2.25" duct	Gray	10
<b>CL-3030</b>	\$24.00	Wire retainer fastener for 3.0" x 3.0" duct	Gray	10
<b>CL-3040</b>	\$24.00	Wire retainer fastener for 3.0" x 4.0" duct	Gray	10
<b>CL-4022</b>	\$26.00	Wire retainer fastener for 4.0" x 2.25" duct	Gray	10
<b>CL-4030</b>	\$24.00	Wire retainer fastener for 4.0" x 3.0" duct	Gray	10
<b>CL-4040</b>	\$16.00	Wire retainer fastener for 4.0" x 4.0" duct	Gray	5
<b>CL-6040</b>	\$20.00	Wire retainer fastener for 6.0" x 4.0" duct	Gray	5




**CL-1515**



# Wiring Duct – Accessories

Duct Marking Tags			
Part Number	Price	Description	Pcs/Pkg
DM1	\$24.00	Single-width white cardboard identification label for wiring duct. Supplied with black plastic mounting clip and transparent plastic cover slide	50


**Note:** DM1 marking tags can only be used with T1 series wire duct.




## Identification Tags

Allowing easy identification of control gear and switchgear, these tags are mounted by snapping the clip onto the sidewall finger segments of the duct. No gluing - no drilling! After installation, they need not be removed during maintenance or any work which involves the removal of the covers.

**Note:** Take care that clip is installed above the wires coming out to the sidewall slots.




Mounting Devices			
Part Number	Price	Description	Pcs/Pkg
ZP1	\$12.00	Round, white polyamide 'button' used to mount components and separators inside duct.	100
ZP2	\$15.00	Square white polyamide cable tie mount used to tighten a wire bundle inside duct.	50




## Mounting Inserts

We carry mounts in two styles: ZP1 for mounting components and SEP-E separators inside duct, or for mounting small sizes of duct inside larger sizes (for separation of circuits with different functions); and ZP2, which is used with a cable tie to secure a wire bundle inside the duct.




Wiring Duct Rivets and Rivet Tools			
Part Number	Price	Description	Pcs/Pkg
R4	\$14.00	Blue polyamide rivet used to install all types of wiring duct with standard 4.5 mm [0.17 in] mounting holes.	250
B4	\$37.00	Red polyamide rivet tool used to install R4 rivets.	1
R6	\$16.00	Natural polyamide rivet used to install all types of wiring duct with standard 6.5 mm [0.26 in] mounting holes.	250
B6	\$37.00	Yellow polyamide rivet tool used to install R6 rivets.	1



## Rivets and Rivet Tools

Wiring duct rivets install quickly and easily with the companion rivet tool, offering good temperature resistance and excellent mechanical properties. They can be used to install all types of wiring duct with standard mounting holes.




# Wiring Duct – Accessories



## Spiral Wrap


For neatly grouping wire bundles simply and economically, spiral wrap has no equal. Strong, yet easy to install, it protects the wire bundle, keeping it flexible though tightly contained. It is easily removed and reusable for temporary wiring.

### Dimensions



Catalog Number		Dimensions in Inches			Wire Bundle Size in Inches	Feet per Carton
<i>Polyethylene</i>	<i>Flame-Retardant Polyethylene</i>	A	B	C		
<b>P-1</b>	<b>PA1</b>	.06	.12	.20	1/16 to 1/2	160
<b>P-2</b>	<b>PA2</b>	.16	.24	.31	¼ to 2	80
<b>P-3</b>	<b>PA3</b>	.31	.39	.47	3/8 to 3	80
<b>P-4</b>	<b>PA4</b>	.35	.47	.47	½ to 4	65

Spiral Wrap				
Part Number	Price	Description	Color	Length
<b>P-1</b>	\$14.00	0.125" nominal o.d. Polyethylene spiral wrap used for wire bundles from 1/16 to 1/2 inch diameter.	Natural	160 ft./pack
<b>PA1</b>	\$20.00	0.125" nominal o.d. self-extinguishing Polyethylene spiral wrap used for wire bundles from 1/16 to 1/2 inch diameter.	White	160 ft./pack
<b>P-2</b>	\$15.00	0.25" nominal o.d. Polyethylene spiral wrap used for wire bundles from 1/4 to 2 inch diameter.	Natural	80 ft./pack
<b>PA2</b>	\$21.00	0.25" nominal o.d. self-extinguishing Polyethylene spiral wrap used for wire bundles from 1/4 to 2 inch diameter.	White	80 ft./pack
<b>P-3</b>	\$24.00	0.375" nominal o.d. Polyethylene spiral wrap used for wire bundles from 3/8 to 3 inch diameter.	Natural	80 ft./pack
<b>PA3</b>	\$37.00	0.375" nominal o.d. self-extinguishing Polyethylene spiral wrap used for wire bundles from 3/8 to 3 inch diameter.	White	80 ft./pack
<b>P-4</b>	\$32.00	0.5" nominal o.d. Polyethylene spiral wrap used for wire bundles from 1/2 to 4 inch diameter.	Natural	65 ft./pack
<b>PA4</b>	\$46.00	0.5" nominal o.d. self-extinguishing Polyethylene spiral wrap used for wire bundles from 1/2 to 4 inch diameter.	White	65 ft./pack



## Braided Sleeving

This lightweight, expandable, self-extinguishing polyester sleeving has an open weave to allow maximum diameter expansion. It is super-flexible and easy to install, gripping objects of various shapes and sizes reliably. Abrasion-resistant, it provides extra protection against chemicals and flame.

Braided Expandable Sleeving Material Specifications	
<b>Operating Temp</b>	-50°C to +150°C (-58°F to +302°F)
<b>Physical Properties</b>	Self-extinguishing for UL 94V-2
<b>Maximum Elongation</b>	42%
<b>Diameter Expansion</b>	100%
<b>Other</b>	Halogen-free

Expandable Sleeving				
Part Number	Price	Description	Color	Length
<b>TY-5</b>	\$95.00	Braided expandable polyester sleeving, 0.197" (5mm) nominal i.d., 0.157" (4mm) to 0.472" (12mm) nominal range	Black	325 ft./pack
<b>TY-10</b>	\$177.00	Braided expandable polyester sleeving, 0.375" (10mm) nominal i.d., 0.315" (8mm) to 0.866" (22mm) nominal range	Black	325 ft./pack
<b>TY-20</b>	\$152.00	Braided expandable polyester sleeving, 0.750" (20mm) nominal i.d., 0.630" (16mm) to 1.378" (35mm) nominal range	Black	164 ft./pack
<b>TY-30</b>	\$219.00	Braided expandable polyester sleeving, 1.125" (30mm) nominal i.d., 0.984" (25mm) to 1.890" (48mm) nominal range	Black	164 ft./pack
<b>TY-50</b>	\$315.00	Braided expandable polyester sleeving, 2.0" (50mm) nominal i.d., 1.575" (40mm) to 2.825" (72mm) nominal range	Black	164 ft./pack

# Wiring Duct – Material Specifications

Material Specifications								
Materials	Test Standard	Unit of Measure	Rigid PVC	Polypropylene	PVC Molded Components	Polyamide 6	Polyethylene	Flame Retardant Polyethylene
Technical Characteristics								
<b>Chemical/Physical Properties</b>								
<b>Specific Gravity</b>	ASTM D792	g/cm <sup>3</sup>	1.55	1.01	1.32	1.14	0.92	0.97
<b>H<sub>2</sub>O 73.4°F Absorption</b>	ISO 62	%	<0.1	0.02	<0.1	2.5	<0.1	<0.1
<b>Formaldehyde</b>	–	ppm	absent	absent	absent	absent	absent	absent
<b>Cadmium</b>	–	ppm	absent	absent	absent	absent	absent	absent
<b>Mechanical Properties</b>								
<b>Tensile Stress at Break</b>	ASTM D638	MPa	39	28	30	45	17	15
<b>Traction Strength</b>	ASTM D638	MPa	44	27	27	55	9.5	9
<b>Elongation at Break</b>	ASTM D638	%	130	200	97	250	400	600
<b>Modulus of Elasticity at Traction</b>	ASTM D638	MPa	4400	n/a	–	950	–	240
<b>Modulus of Elasticity at Flexion</b>	ASTM D790	MPa	3200	2100	–	1100	210	130
<b>Thermal Properties</b>								
<b>Temperature VICAT</b>	ASTM D1525	°C	84	95	70	198	89	–
<b>HDT</b>	ASTM D648	°C	72	60	60	185	–	–
<b>Coefficient of Expansion</b>	ASTM D696	K <sup>-1</sup>	6 10 <sup>-5</sup>	10 <sup>-5</sup>	8 10 <sup>-5</sup>	8-10 10 <sup>-5</sup>	22 10 <sup>-5</sup>	10 <sup>-5</sup>
<b>Specific Heat</b>	ASTM C351	kJ/kgK	0.94	n/a	1.24	1.7	–	–
<b>Thermal Conductivity</b>	ASTM C177	W/mK	0.14	0.21	0.14	0.29	0.32	0.32
<b>Electrical Properties</b>								
<b>Dielectric Constant</b>	ASTM D150	–	3.2 - 4.0	2.5	3.2	5.0	2.4	2.3
<b>Dielectric Strength</b>	IEC 243	kV/mm	70	25	60	35	90	90
<b>Surface Resistance</b>	IEC 93	Ω	10 <sup>13</sup>	10 <sup>13</sup>	10 <sup>13</sup>	5 10 <sup>11</sup>	10 <sup>13</sup>	10 <sup>13</sup>
<b>Self-Extinguishing</b>								
<b>Self-Extinguishing UL 94 1.6 mm</b>	UL 94	–	V-0	V-0	V-0	V-2	HB	V-2
<b>Self-Extinguishing UL 94 3.2 mm</b>	UL 94	–	V-0	V-0	V-0	V-2	HB	V-2
<b>Hot Wire Test (2 mm)</b>	IEC 695-2-1	°C	960	960	960	650	650	850
<b>Oxygen Number</b>	ASTM D2863	%	43	30	34	25	–	25