

Wire - Type THHN

Applications

Type THHN building wire is intended for general purpose applications as defined by the National Electrical Code (NEC). Type THHN is permitted for new construction or rewiring for 600-volt applications. For applications requiring Type THHN, the conductor is appropriate for use in wet or dry locations at temperatures not to exceed 90°C or not to exceed 75°C in oil or coolants. Slick nylon outer jacket for easy pulling. All sizes rated gasoline and oil resistant II. THHN wire 6AWG and larger Sunlight Resistant in all colors.

THHN wire is sold in 500 foot spools; certain sizes are also available in 2500 foot reels.



Features

Conductors

Stranded, uncoated copper conductors per ASTM-B3, ASTM-B787 and ASTM-B8

Insulation

Color-coded Polyvinyl Chloride (PVC), heat and moisture-resistant, flame-retardant compound per UL-1063 and UL-83


Jacket

A tough, polyamide, Nylon outer covering per UL-1063 and UL-83

Standards

- UL Standards UL-83, UL-1063, UL-758
- AWM Spec 1316, 1317, 1318, 1319, 1320, 1321
- ASTM Stranding Class B3, B8, B787
- Federal Specification A-A-59544
- Canadian Standards Association C22.2 No. 75
- NEMA WC70/ICEA S-95-658
- ICEA T-29-520 (210,000 Btu/hr) Flame Test
- ARRA 2009; Section 1605 "Buy American" Compliant
- RoHS

Type THHN Wire



Type THHN Wire Specifications											
Size (AWG or kcmil)	Number of Strands	Cross-sectional Area (mm ²)	Insulation Thickness (inches)		Overall Outside Diameter		Allowable Ampacities*			Approximate Weight (lbs) 500'/2500'	Standard Packaging spool/reel
			PVC	Nylon	(inches)	(mm)	60°C	75°C	90°C		
14	19	6.258	0.015	0.004	0.109	2.77	15	20	25	7.8 / 42.2	500' or 2500'. Some colors not offered in 2500' reel.
12	19	8.581	0.015	0.004	0.127	3.23	20	25	30	11.7 / 61.4	
10	19	13.61	0.015	0.004	0.160	4.07	30	35	40	18.7	500'
8	19	23.61	0.030	0.005	0.212	5.39	40	50	55	31.4	
6	19	32.71	0.030	0.005	0.248	6.30	55	65	75	48.5	
4	19	53.16	0.040	0.006	0.317	8.06	70	85	95	75.4	

**Note: Allowable ampacity shown above is per the National Electric Code. The above data is approximate and subject to normal manufacturing tolerances.*

Please Note: Our prices on wire are closely tied to the market price for copper. This allows us to offer the best savings possible if conditions are favorable; however, it also means that our prices may increase if market conditions warrant.

Wire - Type THHN

Type THHN Wire						
Part Number	Insulation Color	Gauge	Description	Spool/Reel Length	Approx. Weight	Price
THHN14BK	Black	14AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	500'	7.8 lbs	\$62.00
THHN14WH	White					\$62.00
THHN14RD	Red					\$62.00
THHN14BL	Blue					\$62.00
THHN14GN	Green					\$62.00
THHN14YL	Yellow					\$62.00
THHN14OR	Orange					\$62.00
THHN14BN	Brown					\$62.00
THHN14PL	Purple					\$62.00
THHN14GY	Gray					\$62.00
THHN14GYL	Green with Yellow spiral stripe					\$67.00
THHN14BW	Blue with White spiral stripe					\$67.00
THHN12BK	Black					12AWG
THHN12WH	White	\$92.00				
THHN12RD	Red	\$92.00				
THHN12BL	Blue	\$92.00				
THHN12GN	Green	\$92.00				
THHN12YL	Yellow	\$92.00				
THHN12OR	Orange	\$92.00				
THHN12BN	Brown	\$92.00				
THHN12GY	Gray	\$92.00				
THHN12GYL	Green with Yellow spiral stripe	\$97.00				
THHN10BK	Black	10AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	500'	18.7 lbs	\$142.00
THHN10WH	White					\$142.00
THHN10GN	Green					\$142.00
THHN10YL	Yellow					\$142.00
THHN10OR	Orange					\$142.00
THHN10BN	Brown					\$142.00
THHN10GYL	Green with Yellow spiral stripe					\$147.00
THHN8BK	Black	8AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	500'	31.4 lbs	\$239.00
THHN8GN	Green					\$239.00
THHN8GYL	Green with Yellow spiral stripe					\$244.00
THHN6BK	Black	6AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	500'	48.5 lbs	\$363.00
THHN4BK	Black	4AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	500'	75.4 lbs	\$659.00

Wire - Type THHN

Type THHN Wire						
Part Number	Color	Gauge	Description	Spool/Reel Length	Approx. Weight	Price
THHN14BK25	Black	14AWG	Type THHN wire, bare copper, 19 strands, 600 Volts	2500'	42.2 lbs	\$310.00
THHN14WH25	White					\$310.00
THHN14RD25	Red					\$310.00
THHN14BL25	Blue					\$310.00
THHN14GN25	Green					\$310.00
THHN14YL25	Yellow					\$310.00
THHN14OR25	Orange					\$310.00
THHN14BN25	Brown					\$310.00
THHN14PL25	Purple					\$310.00
THHN14GY25	Gray					\$310.00
THHN14BW25	Blue with White spiral stripe					\$335.00
THHN12BK25	Black	12AWG	Type THHN wire, bare copper, 19 strands, 600 Volts		61.4 lbs	\$465.00
THHN12WH25	White					\$465.00
THHN12RD25	Red					\$465.00
THHN12BL25	Blue					\$465.00
THHN12GN25	Green					\$465.00
THHN12YL25	Yellow					\$465.00
THHN12OR25	Orange					\$465.00
THHN12BN25	Brown					\$465.00

Gauge Conversion Table

American Wire Gauge Conversion Chart*			
This cross reference shows equivalent nominal values. Actual cross sections may vary.			
AWG	mm ²	AWG	mm ²
30	0.05	6	16
28	0.08	4	25
26	0.14	2	35
24	0.25	1	50
22	0.34	1/0	55
21	0.38	2/0	70
20	0.50	3/0	95
18	0.75	4/0	120
17	1.00	300MCM	150
16	1.50	350MCM	185
14	2.50	500MCM	240
12	4	600MCM	300
10	6	750MCM	400
8	10	1000MCM	500

**Note: Table shows commercially used equivalent values.*