


# IronHorse<sup>®</sup> Cast-Iron Worm Gearboxes

## Cast-Iron Model Overview




***IronHorse Cast-Iron  
Right-Hand Shaft  
Worm Gearbox***



***IronHorse Cast-Iron  
Left-Hand Shaft  
Worm Gearbox***



***IronHorse Cast-Iron  
Dual Shaft  
Worm Gearbox***



***IronHorse Cast-Iron  
Hollow Bore  
Worm Gearbox***

## Gearbox Overview

Gearboxes, also known as enclosed gear drives or speed reducers, are mechanical drive components that can control a load at a reduced fixed ratio of the motor speed. The output torque is also increased by the same ratio, while the horsepower remains the same (less efficiency losses.) For example, a 10:1 ratio gearbox outputs approximately the same motor output horsepower, motor speed divided by 10, and motor torque multiplied by 10.

Worm gearboxes contain a worm (gear type) on the input shaft, and a mating gear on the output shaft. Worm gearboxes also change the drive direction by 90°.

IronHorse worm gearboxes are manufactured in an ISO9001 certified plant by one of the leading gearbox manufacturers in the world today. Only the highest quality materials are tested, certified, and used in the manufacturing process. Strict adherence to and compliance with the toughest international and U.S. testing standards and manufacturing procedures assure you the highest quality products.

As seen above, our cast-iron gearboxes are offered with right-hand, left-hand and dual (both right and left) output shafts, and with hollow-bore outputs (all the way through from one side to the other). We also offer optional gearbox mounting bases for ease of installation.

## Features

- C flange input; dual shaft, right-hand shaft, left-hand shaft or hollow-bore output
- Cast iron one-piece housing
- 1045 carbon steel shaft
- AlBC3 (aluminum bronze casting) main gear; much harder than the typical phosphor bronze
- Shaft sleeves protect all shafts
- One-piece output shaft hub secures output shaft bearing
- Double bearing sets on both shaft ends
- Heavy duty bearings on the output shaft
- Interior channel guides oil to directly and constantly lube bearings
- All units filled with Mobil SHC634 synthetic oil
- Double-lipped embedded oil seals to prevent leakage
- Special anti-rust primer inside and outside the gearbox
- Special black natural dry paint
- Universally interchangeable compact design ensures easy OEM replacement
- Multiple mounting orientation options (see user manual for allowed mounting orientations)
- Radiused mounting holes
- Optional mounting plates available
- One year warranty

## Applications

- Use with electric motors for reducing output speed, increasing torque, changing drive direction, or running two loads from one motor.
- Use for conveyors, packaging machines, rotary tables, etc.

# IronHorse® Cast-Iron Worm Gearboxes

## Specifications

IronHorse Cast-Iron Worm Gearbox Specifications																				
Part Number *	Price	Nominal Ratio	Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP 1 @ 1800 RPM	NEMA Motor Frame	Output Type 2	Center Distance 3 (in)	Overhung Load 4 (lb)	Thrust Load 5 (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input *						Maximum Backlash (arc-minute)	
													Mechanical 6			Thermal 7				
													Input Power (hp)	Output Power (hp)	Output Torque (lb-in)	Input Power (hp)	Output Power (hp)	Output Torque (lb-in)		
WG-175-005-D	\$174.00	5:1	5.25:1	350	1-1/2	56C	D	1.75	650	550	93	23	2.83	2.62	499	2.28	2.11	402	20	
WG-175-005-H	\$215.00																			H
WG-175-005-R	\$174.00																			R
WG-175-005-L	\$173.00																			L
WG-175-010-D	\$174.00	10:1	10.33:1	175	1	56C	D	1.75	650	550	88	23	1.57	1.38	515	1.36	1.19	445		
WG-175-010-H	\$215.00																			H
WG-175-010-R	\$174.00																			R
WG-175-010-L	\$173.00																			L
WG-175-015-D	\$174.00	15:1	14.5:1	117	3/4	56C	D	1.75	650	550	85	23	1.24	1.06	554	1.13	0.96	506		
WG-175-015-H	\$215.00																			H
WG-175-015-R	\$174.00																			R
WG-175-015-L	\$173.00																			L
WG-175-020-D	\$174.00	20:1	19.5:1	88	3/4	56C	D	1.75	650	550	83	23	1.26	1.04	737	0.98	0.81	572		
WG-175-020-H	\$215.00																			H
WG-175-020-R	\$174.00																			R
WG-175-020-L	\$173.00																			L
WG-175-040-D	\$174.00	40:1	40:1	44	1/3	56C	D	1.75	650	550	62	23	0.79	0.49	714	0.45	0.28	404		
WG-175-040-H	\$228.00																			H
WG-175-040-R	\$174.00																			R
WG-175-040-L	\$173.00																			L
WG-175-060-D	\$174.00	60:1	60:1	29	1/4	56C	D	1.75	650	550	52	23	0.38	0.20	433	0.35	0.19	404		
WG-175-060-H	\$228.00																		H	
WG-175-060-R	\$174.00																		R	
WG-175-060-L	\$173.00																		L	
WG-206-005-D	\$221.00	5:1	5.75:1	350	2	56C	D	2.06	700	750	92	28	3.62	3.33	925	2.57	2.36	657	21	
WG-206-005-H	\$275.00																			H
WG-206-005-R	\$221.00																			R
WG-206-005-L	\$219.00																			L
WG-206-010-D	\$221.00	10:1	10.33:1	175	1-1/2	56C	D	2.06	700	750	90	28	2.77	2.50	935	2.10	1.89	708		
WG-206-010-H	\$275.00																			H
WG-206-010-R	\$221.00																			R
WG-206-010-L	\$219.00																			L
WG-206-015-D	\$221.00	15:1	15.5:1	117	1	56C	D	2.06	700	750	85	28	2.09	1.78	1002	1.40	1.20	673		
WG-206-015-H	\$275.00																			H
WG-206-015-R	\$221.00																			R
WG-206-015-L	\$219.00																			L
WG-206-020-D	\$208.00	20:1	19.5:1	88	1	56C	D	2.06	700	750	82	28	1.57	1.29	914	1.17	0.96	681		
WG-206-020-H	\$275.00																			H
WG-206-020-R	\$221.00																			R
WG-206-020-L	\$221.00																			L

\* Maximum Input Speed is 2500 rpm.

( table continued next page )

# IronHorse<sup>®</sup> Cast-Iron Worm Gearboxes

## Specifications (continued)

<i>IronHorse Cast-Iron Worm Gearbox Specifications ( continued from previous page )</i>																						
Part Number *	Price	Nominal Ratio	Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP <sup>1</sup> @ 1800 RPM	NEMA Motor Frame	Output Type <sup>2</sup>	Center Distance <sup>3</sup> (in)	Overhung Load <sup>4</sup> (lb)	Thrust Load <sup>5</sup> (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input *						Maximum Backlash (arc-minute)			
													Mechanical <sup>6</sup>			Thermal <sup>7</sup>						
													Input Power (hp)	Output Power (hp)	Output Torque (lb-in)	Input Power (hp)	Output Power (hp)	Output Torque (lb-in)				
WG-206-040-D	\$210.00	40:1	40:1	44	1/2	56C	D	2.06	700	750	71	28	1.09	0.77	1120	0.71	0.50	726	21			
WG-206-040-H	\$275.00						H													27		
WG-206-040-R	\$221.00						R															
WG-206-040-L	\$221.00						L															
WG-206-060-D	\$208.00	60:1	60:1	29	1/3	56C	D	2.06	700	750	58	28	0.60	0.35	750	0.48	0.28	606		17		
WG-206-060-H	\$275.00						H														27	
WG-206-060-R	\$221.00						R															
WG-206-060-L	\$221.00						L															
WG-237-005-D	\$251.00	5:1	5.25:1	350	3	56C	D	2.37	900	900	93	38	4.32	4.02	766	3.56	3.31	630			17	
WG-237-005-H	\$314.00						H															37
WG-237-005-R	\$265.00						R															
WG-237-005-L	\$265.00						L															
WG-237-010-D	\$251.00	10:1	10.33:1	175	1-1/2	56C	D	2.37	900	900	89	38	3.47	3.09	1158	2.24	1.99	746	17			
WG-237-010-H	\$314.00						H															37
WG-237-010-R	\$265.00						R															
WG-237-010-L	\$263.00						L															
WG-237-015-D	\$251.00	15:1	15.5:1	117	1	56C	D	2.37	900	900	84	38	2.64	2.22	1249	1.55	1.30	732		17		
WG-237-015-H	\$314.00						H															37
WG-237-015-R	\$265.00						R															
WG-237-015-L	\$263.00						L															
WG-237-020-D	\$251.00	20:1	20:1	88	1	56C	D	2.37	900	900	82	38	2.06	1.69	1195	1.36	1.12	791			17	
WG-237-020-H	\$314.00						H															37
WG-237-020-R	\$265.00						R															
WG-237-020-L	\$263.00						L															
WG-237-040-D	\$251.00	40:1	40:1	44	1/2	56C	D	2.37	900	900	71	38	1.45	1.02	1483	0.83	0.58	845	17			
WG-237-040-H	\$314.00						H															37
WG-237-040-R	\$265.00						R															
WG-237-040-L	\$263.00						L															
WG-237-060-D	\$251.00	60:1	60:1	29	1/2	56C	D	2.37	900	900	61	38	0.86	0.53	1149	0.63	0.39	844		17		
WG-237-060-H	\$314.00						H															37
WG-237-060-R	\$265.00						R															
WG-237-060-L	\$263.00						L															
WG-262-005-D	\$268.00	5:1	5.25:1	350	3	182TC	D	2.62	1000	1000	93	57	5.24	4.86	924	4.32	4.00	761			17	
WG-262-005-H	\$387.00						H															56
WG-262-005-R	\$287.00						R															
WG-262-005-L	\$282.00						L															
WG-262-010-D	\$268.00	10:1	10.67:1	175	2	182TC	D	2.62	1000	1000	90	57	4.17	3.74	1445	3.06	2.75	1061	17			
WG-262-010-H	\$387.00						H															56
WG-262-010-R	\$287.00						R															
WG-262-010-L	\$282.00						L															

\* Maximum Input Speed is 2500 rpm.

( table continued next page )

# IronHorse® Cast-Iron Worm Gearboxes

## Specifications (continued)

<b>IronHorse Cast-Iron Worm Gearbox Specifications ( continued from previous page )</b>																				
Part Number *	Price	Nominal Ratio	Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP 1 @ 1800 RPM	NEMA Motor Frame	Output Type 2	Center Distance 3 (in)	Overhung Load 4 (lb)	Thrust Load 5 (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input *						Maximum Backlash (arc-minute)	
													Mechanical 6			Thermal 7				
													Input Power (hp)	Output Power (hp)	Output Torque (lb-in)	Input Power (hp)	Output Power (hp)	Output Torque (lb-in)		
WG-262-015-D	\$268.00	15:1	15.5:1	117	2	56C	D	2.62	1000	1000	87	50	3.22	2.81	1577	2.47	2.16	1212	17	
WG-262-015-H	\$387.00						H													50
WG-262-015-R	\$287.00						R													
WG-262-015-L	\$282.00						L													
WG-262-020-D	\$268.00	20:1	19.5:1	88	1-1/2	56C	D	2.62	1000	1000	83	50	2.67	2.21	1563	1.84	1.53	1078		
WG-262-020-H	\$387.00						H													50
WG-262-020-R	\$287.00						R													
WG-262-020-L	\$282.00						L													
WG-262-040-D	\$268.00	40:1	40:1	44	3/4	56C	D	2.62	1000	1000	72	50	1.85	1.32	1919	1.11	0.80	1153		
WG-262-040-H	\$387.00						H													50
WG-262-040-R	\$287.00						R													
WG-262-040-L	\$282.00						L													
WG-262-060-D	\$268.00	60:1	60:1	29	3/4	56C	D	2.62	1000	1000	66	50	1.16	0.77	1670	0.94	0.62	1346		
WG-262-060-H	\$387.00						H													51
WG-262-060-R	\$287.00						R													
WG-262-060-L	\$282.00						L													
WG-325-010-DC	\$423.00	10:1	10.33:1	175	3	182/4TC	D	3.25	1200	1100	90	91	7.19	6.46	2419	4.63	4.16	1558		
WG-325-010-HC	\$555.00						H												90	
WG-325-010-LC	\$423.00						L													
WG-325-010-RC	\$423.00						R													
WG-325-015-DC	\$423.00	15:1	15.5:1	117	5	182/4TC	D	3.25	1200	1100	85	91	5.45	4.65	2611	3.19	2.72	1527		
WG-325-015-HC	\$555.00						H												90	
WG-325-015-LC	\$423.00						L													
WG-325-015-RC	\$423.00						R													
WG-325-020-DC	\$423.00	20:1	19.5:1	88	3	182TC	D	3.25	1200	1100	86	91	4.74	4.07	2875	3.31	2.85	2011		
WG-325-020-HC	\$555.00						H												90	
WG-325-020-LC	\$423.00						L													
WG-325-020-RC	\$423.00						R													
WG-325-030-DA	\$423.00	30:1	30:1	58	2	56C	D	3.25	1200	1100	77	88	3.66	2.80	3045	2.00	1.53	1661		
WG-325-030-DB	\$423.00					145TC	D												88	
WG-325-030-HA	\$555.00					56C	H													
WG-325-030-HB	\$555.00					145TC	H													
WG-325-030-LA	\$423.00					56C	L													
WG-325-030-LB	\$423.00					145TC	L													
WG-325-030-LC	\$423.00				3	182TC	L	87												
WG-325-030-RA	\$423.00				2	56C	R													
WG-325-030-RB	\$423.00				2	145TC	R													
WG-325-030-RC	\$423.00				3	182TC	R													

\* Maximum Input Speed is 2500 rpm.

( table continued next page )

# IronHorse<sup>®</sup> Cast-Iron Worm Gearboxes

## Specifications (continued)

IronHorse Cast-Iron Worm Gearbox Specifications ( continued from previous page )																				
Part Number *	Price	Nominal Ratio	Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP <sup>1</sup> @ 1800 RPM	NEMA Motor Frame	Output Type <sup>2</sup>	Center Distance <sup>3</sup> (in)	Overhung Load <sup>4</sup> (lb)	Thrust Load <sup>5</sup> (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input *					Maximum Backlash (arc-minute)		
													Mechanical <sup>6</sup>			Thermal <sup>7</sup>				
													Input Power (hp)	Output Power (hp)	Output Torque (lb-in)	Input Power (hp)	Output Power (hp)		Output Torque (lb-in)	
WG-325-040-DA	\$423.00	40:1	40:1	44	1-1/2	56C	D	3.25	1200	1100	76	88	3.35	2.55	3692	1.96	1.49	2156	15	
WG-325-040-DB	\$423.00					145TC	D													88
WG-325-040-HA	\$555.00					56C	H													87
WG-325-040-HB	\$555.00					145TC	H													87
WG-325-040-LA	\$423.00					56C	L													87
WG-325-040-LB	\$423.00					145TC	L													87
WG-325-040-RA	\$423.00					56C	R													87
WG-325-040-RB	\$423.00					145TC	R													87
WG-325-060-DA	\$423.00					60:1	60:1													29
WG-325-060-DB	\$423.00	145TC	D	88																
WG-325-060-HA	\$555.00	56C	H	87																
WG-325-060-HB	\$555.00	145TC	H	87																
WG-325-060-LA	\$423.00	56C	L	87																
WG-325-060-LB	\$423.00	145TC	L	87																
WG-325-060-RA	\$423.00	56C	R	87																
WG-325-060-RB	\$423.00	145TC	R	87																

\* Maximum Input Speed is 2500 rpm.

- Nominal Motor HP is the highest hp 1800 rpm motor to be used with the gearbox under conditions of 1.0 service factor. Gearbox input power capacity decreases as motor speed decreases and as service factor increases.
- Output Type: D = Dual Shaft; H = Hollow Bore; R = Right-Hand Shaft; L = Left-Hand Shaft
- The Center Distance is the distance between the centerlines of the input and output shafts.
- Overhung Load ratings are for forces perpendicular to the output shaft and located at the shaft midpoint, such as from a gear, pulley, or sprocket with a belt or chain. Divide OHL ratings by the applicable OHL K factors shown separately in the Selection Factors tables. OHL ratings should also be divided by applicable service factors.
- Thrust Load ratings are for forces along the axis of the output shaft, usually encountered in vertical-drive applications from agitators, mixers, fans, blowers, etc.
- Maximum Mechanical Ratings are limits based on strength and durability of gearbox components; applicable when operating time is short and stopped time is greater than or equal to operating time. These ratings are applicable for 1.0 service factor loads, and may require modification depending upon characteristics of the applicable driven loads. Refer to the "Service Factors" table for more information.
- Maximum Thermal Ratings are limits for gearbox continuous use without overheating.

## Gearbox Selection Factors

Overhung Load K Factors for Various Drive Types	
Chain & Sprocket	1.00
Gear	1.25
V-belt	1.50
Flat Belt	2.50
Variable Pitch Belt	3.50

Divide gearbox OHL ratings by the applicable OHL K factors.

Service Factors for Selecting Gearboxes (when used with electric motors)				
Service Continuity (per day)	Load Characteristics			
	Uniform	Moderate Shock*	Heavy Shock*	Extreme Shock*
Occasional 1/2 hour	1.00	1.00	1.00	1.25
Less than 3 hours	1.00	1.00	1.25	1.50
3-10 hours	1.00	1.25	1.50	1.75
More than 10 hours	1.25	1.50	1.75	2.00

\* Shock results from sudden increases in the torque demand of the load, such as: sudden stopping, restarting, and/or reversing; significantly heavy loads dropped onto a moving conveyor; impact loads such as punch press operations.

Depending upon the load characteristics, divide the gearbox HP, Overhung Load, and Maximum Mechanical Capacity ratings by the applicable service factor.

# IronHorse<sup>®</sup> Aluminum Worm Gearboxes

## Aluminum Model Overview



**IronHorse Aluminum Hollow Bore  
Worm Gearbox**



**IronHorse Aluminum Worm Gearbox  
Accessories**

## Gearbox Overview

Gearboxes, also known as enclosed gear drives or speed reducers, are mechanical drive components that can control a load at a reduced fixed ratio of the motor speed. The output torque is also increased by the same ratio, while the horsepower remains the same (less efficiency losses.) For example, a 10:1 ratio gearbox outputs approximately the same motor output horsepower, motor speed divided by 10, and motor torque multiplied by 10.

Worm gearboxes contain a worm (gear type) on the input shaft, and a mating gear on the output shaft. Worm gearboxes also change the drive direction by 90°.

IronHorse worm gearboxes are manufactured in an ISO9001 certified plant by one of the leading gearbox manufacturers in the world today. Only the highest quality materials are tested, certified, and used in the manufacturing process. Strict adherence to and compliance with the toughest international and U.S. testing standards and manufacturing procedures assure you the highest quality products.

Aluminum gearboxes feature hollow-bore outputs (hollow all the way through from one side to the other). These gearboxes also utilize C-face mounting interfaces for trouble-free connections to C-face motors. We also offer optional single and double output shafts, output flanges, torque arms, and output covers.

## Features

- 10:1 to 100:1 ratios
- Box sizes 30 to 75 mm
- Aluminum alloy housing for lightweight design
- Hardened worm shaft for increased durability
- Two bearings on input and output shafts
- NEMA motor input flanges
- All units filled with Mobil SHC634 synthetic oil
- No vent plug or breather needed; maintenance-free reducer
- Double lip oil seals prevent leakage
- Multiple mounting holes for all angle mounts
- Epoxy paint applied to inside and outside of reducer to protect against corrosion
- Hollow output bores with available plug-in output shafts
- Multiple mounting orientation options (see user manual for allowed mounting orientations)
- Single and Double Output Shaft material: S45C
- Single and Double Output Shaft Hardness: HBS220~260

## Applications

- Use with electric motors for reducing output speed, increasing torque, changing drive direction, or running two loads from one motor.
- Use for conveyors, packaging machines, rotary tables, etc.

# IronHorse<sup>®</sup> Aluminum Worm Gearboxes

## Specifications

IronHorse Aluminum Worm Gearbox Specifications – 30, 40, 50, & 63 mm Frames																	
Part Number	Price	Nominal / Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP <sup>1</sup> @1800 rpm	NEMA Motor Frame	Output Type <sup>2</sup>	Center Distance <sup>3</sup> (mm)	Overhung Load <sup>4</sup> (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input			Maximum Input Speed (rpm)	Maximum Backlash (arc-minute)		
											Mechanical <sup>5</sup>						
											Input Power (hp)	Output Power (hp)	Output Torque (lb-in)				
WGA-30M-010-H1	\$104.00	10:1	175	0.5	56C	H	30	142	80	3	0.54	0.43	150	28.8			
WGA-30M-020-H1	\$104.00	20:1	88	0.25							0.30	0.22	150	28.2			
WGA-30M-030-H1	\$104.00	30:1	58	0.25							0.25	0.16	177	28.8			
WGA-30M-040-H1	\$104.00	40:1	44	0.2							0.19	0.10	150	28.2			
WGA-30M-060-H1	\$104.00	60:1	29	0.12							0.12	0.06	142	25.8			
WGA-40M-010-H1	\$129.00	10:1	175	1	56C	H	40	279	83	5	1.15	0.95	354	24.0			
WGA-40M-020-H1	\$129.00	20:1	88	0.5							0.61	0.48	345				
WGA-40M-030-H1	\$129.00	30:1	58	0.5							0.53	0.36	389				
WGA-40M-040-H1	\$129.00	40:1	44	0.33							0.39	0.25	363				
WGA-40M-060-H1	\$129.00	60:1	29	0.25							0.25	0.14	319				
WGA-40M-080-H1	\$129.00	80:1	22	0.12	56C	H	50	556	50	8	0.19	0.10	283	21.6			
WGA-40M-100-H1	\$129.00	100:1	17.5	0.12							0.15	0.07	257				
WGA-50M-010-H1	\$178.00	10:1	175	2							406	84	2.06		1.73	628	19.2
WGA-50M-020-H1	\$178.00	20:1	88	1							510	78	1.13		0.88	646	17.4
WGA-50M-030-H1	\$178.00	30:1	58	0.75							586	70	0.95		0.67	734	19.2
WGA-50M-040-H1	\$178.00	40:1	44	0.75	56C	H	63	643	65	13	0.70	0.46	664	17.4			
WGA-50M-060-H1	\$178.00	60:1	29	0.33							739	57	0.46		0.26	602	
WGA-50M-080-H1	\$178.00	80:1	22	0.33							810	50	0.38		0.19	566	
WGA-50M-100-H1	\$178.00	100:1	17.5	0.25							866	46	0.28		0.13	487	
WGA-63M-010-H1	\$229.00	10:1	175	3							510	86	3.67		3.16	1141	17.4
WGA-63M-010-H2	\$229.00	10:1	175	3	145TC	510	86	3.67	3.16	1141	13.8						
WGA-63M-020-H1	\$229.00	20:1	88	2	56C	641	80	2.04	1.63	1186							
WGA-63M-020-H2	\$229.00	20:1	88	2	145TC	641	80	2.04	1.63	1186							
WGA-63M-030-H1	\$229.00	30:1	58	1.5	56C	736	73	1.76	1.28	1416							
WGA-63M-040-H1	\$229.00	40:1	44	1	807	70	1.26	0.88	1274								
WGA-63M-060-H1	\$229.00	60:1	29	0.75	928	59	0.86	0.51	1141	13.8							
WGA-63M-080-H1	\$229.00	80:1	22	0.5	1017	53	0.67	0.36	1071								
WGA-63M-100-H1	\$229.00	100:1	18	0.5	1088	48	0.57	0.27	1035								

1) Nominal Motor HP is the highest HP 1800 rpm motor to be used with the gearbox under conditions of 1.0 service factor. Gearbox input power capacity decreases as motor speed decreases and as service factor increases.

2) Output Type: H = Hollow Bore.

3) The Center Distance is the distance between the centerlines of the input and output shafts/bores; serves as the gearbox frame size.

4) Overhung Load ratings are for forces perpendicular to the output shaft and located at the shaft midpoint, such as from a gear, pulley, or sprocket with a belt or chain. Divide OHL ratings by the applicable OHL K factors shown separately in the Selection Factors tables. OHL ratings should also be divided by applicable service factors.

5) Maximum Mechanical Ratings are limits based on strength and durability of gearbox components; applicable when operating time is short and stopped time is greater than or equal to operating time. These ratings are applicable for 1.0 service factor loads, and may require modification depending upon characteristics of the applicable driven loads. Refer to the "Service Factors" table for more information.

# IronHorse<sup>®</sup> Aluminum Worm Gearboxes

## Specifications (continued)

IronHorse Aluminum Worm Gearbox Specifications – 75 mm Frames																
Part Number	Price	Nominal / Actual Ratio	Output RPM @ 1750 RPM Input	Nominal Motor HP <sup>1</sup> @ 1800 rpm	NEMA Motor Frame	Output Type <sup>2</sup>	Center Distance <sup>3</sup> (mm)	Overhung Load <sup>4</sup> (lb)	Efficiency (%)	Approx Weight (lb)	Maximum Ratings @ 1750 RPM Input			Maximum Input Speed (rpm)	Maximum Backlash (arc-minute)	
											Mechanical <sup>5</sup>					
											Input Power (hp)	Output Power (hp)	Output Torque (lb-in)			
WGA-75M-010-H1	\$333.00	10:1	175	5	56C	H	75	604	86	19	5.44	4.68	1717	2,000	16.2	
WGA-75M-010-H2	\$333.00	10:1	175	5	145TC						5.44	4.68	1717			
WGA-75M-010-H3	\$333.00	10:1	175	5	182/4TC						5.44	4.68	1717			
WGA-75M-020-H1	\$333.00	20:1	88	3	56C						759	79	3.14	2.48	1849	14.4
WGA-75M-020-H2	\$333.00	20:1	88	3	145TC						759	79	3.14	2.48	1849	
WGA-75M-030-H1	\$333.00	30:1	58	2	56C						873	72	2.48	1.79	2026	16.2
WGA-75M-040-H1	\$333.00	40:1	44	1.5							957	68	1.88	1.28	1947	14.4
WGA-75M-060-H1	\$333.00	60:1	29	1							1099	62	1.26	0.78	1770	12.6
WGA-75M-080-H1	\$333.00	80:1	22	0.75							1205	58	0.97	0.56	1672	
WGA-75M-100-H1	\$333.00	100:1	18	0.75							1289	52	0.80	0.42	1593	

1) Nominal Motor HP is the highest HP 1800 rpm motor to be used with the gearbox under conditions of 1.0 service factor. Gearbox input power capacity decreases as motor speed decreases and as service factor increases.

2) Output Type: H = Hollow Bore.

3) The Center Distance is the distance between the centerlines of the input and output shafts/bores; serves as the gearbox frame size.

4) Overhung Load ratings are for forces perpendicular to the output shaft and located at the shaft midpoint, such as from a gear, pulley, or sprocket with a belt or chain. Divide OHL ratings by the applicable OHL K factors shown separately in the Selection Factors tables. OHL ratings should also be divided by applicable service factors.

5) Maximum Mechanical Ratings are limits based on strength and durability of gearbox components; applicable when operating time is short and stopped time is greater than or equal to operating time. These ratings are applicable for 1.0 service factor loads, and may require modification depending upon characteristics of the applicable driven loads. Refer to the "Service Factors" table for more information.

### Gearbox Selection Factors

Chain & Sprocket	1.00
Gear	1.25
V-belt	1.50
Flat Belt	2.50
Variable Pitch Belt	3.50

Divide gearbox OHL ratings by the applicable OHL K factors.

Service Continuity (per day)	Load Characteristics			
	Uniform	Moderate Shock*	Heavy Shock*	Extreme Shock*
Occasional 1/2 hour	1.00	1.00	1.00	1.25
Less than 3 hours	1.00	1.00	1.25	1.50
3-10 hours	1.00	1.25	1.50	1.75
More than 10 hours	1.25	1.50	1.75	2.00

\* Shock results from sudden increases in the torque demand of the load, such as: sudden stopping, restarting, and/or reversing; significantly heavy loads dropped onto a moving conveyor; impact loads such as punch press operations.

Depending upon the load characteristics, divide the gearbox HP, Overhung Load, and Maximum Mechanical Capacity ratings by the applicable service factor.



# IronHorse® Worm Gearboxes

## Gearbox Selection

### Gearbox Selection Steps

- 1) Determine the torque and speed required for the load.
- 2) Determine the overall speed ratio of motor speed to load speed.
- 3) Determine the gearbox ratio as well as any reduction outside the gearbox (pulleys, gears, etc.).
- 4) Determine the applicable service factor and overhung load K factor.
- 5) Determine the gearbox real output torque required, and select a gearbox with a higher Maximum Thermal output Torque rating (for WG cast-iron gearboxes; not applicable for WGA aluminum gearboxes).
- 6) Determine the gearbox design output torque required (torque with service factor applied), and select a gearbox with a higher Maximum Mechanical Output Torque rating. (Gearbox must also meet requirement #5.)
- 7) Determine the required sizes of pulleys, gears, etc., and determine the overhung load force. Select a gearbox with a higher Overhung Load rating. (Gearbox must also meet requirements #5 & #6.)
- 8) Confirm that the selected gearbox meets the applicable system requirements.
- 9) Select a compatible motor.

### Gearbox Selection Example (Refer to the specifications tables for gearbox specifications, service factors, and K factors.)

A conveyor will run 10 hours/day with moderate shock loading. The conveyor will be driven by a V-belt and needs to be driven at approximately 20 rpm. The motor to be used will have a nominal speed of 1800 rpm (1725 rpm actual speed). The conveyor will require 2700 in-lb of torque.

- 1) Required **torque** = 2700 in-lb; required **speed** = 20 rpm.
- 2) Determine the **overall speed ratio** of motor speed to load speed:  
Overall speed ratio = motor speed / load speed = 1725 / 20 = 86.25 [about 86:1]
- 3) Determine **pulley ratios** at available **gearbox ratios**:  

$$\text{Gearbox ratio} = (\text{overall speed ratio}) / (\text{pulley ratio})$$

$$\text{Pulley ratio} = (\text{overall speed ratio}) / (\text{gearbox ratio})$$

For **5:1 gearbox**: pulley ratio = 86.25 / 5 = **17.25** [17.25" pulley ratio is prohibitively large]  
 For 10:1 gearbox: pulley ratio = 86.25 / 10 = 8.63  
 For 15:1 gearbox: pulley ratio = 86.25 / 15 = 5.75  
 For 20:1 gearbox: pulley ratio = 86.25 / 20 = 4.31  
 For 30:1 gearbox: pulley ratio = 86.25 / 30 = 2.88  
 For 40:1 gearbox: pulley ratio = 86.25 / 40 = 2.16  
 For 60:1 gearbox: pulley ratio = 86.25 / 60 = 1.44  

$$\text{Pulley ratio} = (\text{conveyor pulley diameter}) / (\text{gearbox pulley diameter})$$
- 4) Determine **service factor (SF)** and **overhung load factor (K)** from applicable tables:  
 SF = 1.25 due to moderate shock loading and 3-10 hours/day operation  
 K = 1.5 due to V-belt
- 5) Use specifications table to select gearbox with **Maximum Thermal\* Torque rating > required real torque**:  
 Gearbox required real torque = (final torque) / (pulley ratio)  

For 10:1 gearbox:	(2700 in-lb) / 8.63 = 312.86 in-lb;	use WG-175-x or larger
For 15:1 gearbox:	(2700 in-lb) / 5.75 = 469.57 in-lb;	use WG-175-x or larger
For 20:1 gearbox:	(2700 in-lb) / 4.31 = 626.45 in-lb;	use WG-206-x or larger
For 30:1 gearbox:	(2700 in-lb) / 2.88 = 937.50 in-lb;	use WG-325-x or WGA-63M*
For 40:1 gearbox:	(2700 in-lb) / 2.16 = 1250.0 in-lb;	use WG-325-x
For 60:1 gearbox:	(2700 in-lb) / 1.44 = 1875.0 in-lb;	use WG-325-x

\* Aluminum gearboxes do not have thermal ratings; use mechanical ratings.
- 6) Use specifications table to select gearbox with **Maximum Mechanical Torque rating > required design torque**:  
 Gearbox required design torque = (real gearbox torque)(service factor)  

For 10:1 gearbox:	(312.86 in-lb)(1.25) = 391.08 in-lb;	use WG-175-x or larger
For 15:1 gearbox:	(469.57 in-lb)(1.25) = 586.96 in-lb;	use WG-206-x or larger
For 20:1 gearbox:	(626.45 in-lb)(1.25) = 783.06 in-lb;	use WG-206-x or larger
For 30:1 gearbox:	(937.50 in-lb)(1.25) = 1171.88 in-lb;	use WG-325-x or WGA-63M or larger
For 40:1 gearbox:	(1250.0 in-lb)(1.25) = 1562.50 in-lb;	use WG-325-x
For 60:1 gearbox:	(1875.0 in-lb)(1.25) = 2343.75 in-lb;	use WG-325-x

(continued on next page)

## IronHorse® Worm Gearboxes

### Gearbox Selection Example (continued)

(Refer to the specifications tables for gearbox specifications, service factors, and K factors.)

[Load requirements: Conveyor to run 10 hours/day; moderate shock loading; driven by V-belt @ approx 20 rpm; requires 2700 in-lb of torque. Motor speed 1725 rpm (1800 rpm nominal).]

7) Use the gearbox overhung load ratings from the specifications table to determine the minimum allowable pulley diameters.

Select gearbox with **Overhung Load rating > overhung load force:**

Gearbox required OHL rating = (gearbox real torque)(K)(SF)/(gearbox pulley diameter / 2)

Minimum gearbox pulley diameter = (T)(K)(SF)(2)/(OHL rating)

Conveyor pulley diameter = (gearbox pulley diameter)(pulley ratio)

For 10:1, WG-175-010-x gearbox:

Minimum gearbox pulley diameter = (312.86 in-lb)(1.5)(1.25)(2)/(650 lb) = 1.8" [use 2"]

Conveyor pulley diameter = (2")(8.63) = ~~17.26"~~ [17.26" pulley size is prohibitively large]

Determine pulley sizes and OHL for next larger gearbox ratio.

For 15:1, WG-206-015-x gearbox:

Minimum gearbox pulley diameter = (469.57 in-lb)(1.5)(1.25)(2)/(700 lb) = 2.5" [use 2.5"]

Conveyor pulley diameter = (2.5")(5.75) = 14.38" [use 14.4"]

Select **WG-206-015-x gearbox, 2.5" gearbox pulley, and 14.4" conveyor pulley.**

For 20:1, WG-206-020-x gearbox:

N/A – larger ratio of same frame size GB is same price, yet provides lower efficiency and power characteristics

For 30:1, WGA-63M-030-H1 gearbox:

Minimum gearbox pulley diameter = (937.50 in-lb)(1.5)(1.25)(2)/(736 lb) = 4.78" [use 5"]

Conveyor pulley diameter = (5")(2.88) = 14.40" [use 14.4"]

N/A – WGA-63M & WG-325 gearboxes costs more than WG-206

For 40:1, N/A – WG-325-xxx gearboxes cost more than WG-206 at any ratio

For 60:1, N/A – WG-325-xxx gearboxes cost more than WG-206 at any ratio

8) **Check results** against original speed and torque requirements:

a) Conveyor speed = (motor speed) / (gearbox ratio)(pulley ratio) = (1725 rpm) / (15)(14.4"/2.5") = 20 rpm

b) Maximum real torque available at conveyor = (gearbox thermal torque)(pulley ratio) = (673 in-lb)(14.4"/2.5") = 3876 in-lb

c) Maximum design torque available at conveyor = (gearbox mechanical torque)(pulley ratio) / (service factor)  
= (1002 in-lb)(14.4"/2.5") / 1.25 = 4617 in-lb

The speed is correct as required, and both maximum torque values are greater than the 2700 in-lb required by the load.

9) **Select a motor** and check torque transmitted to the load:

From the gearbox spec tables, WG-206-015-x efficiency = 85%.

maximum thermal input power = 1.40 hp

maximum mechanical input power @ 1.0 SF = 2.09 hp

maximum mechanical input power @ 1.25 SF = (rated max mechanical input power) / (SF) = 2.09 hp / 1.25 = 1.67 hp

maximum allowable motor power = 1.40 hp; select nominal 1hp motor

Select **1hp motor**, and check for adequate torque at the load:

Torque = Power / Speed [conversion factor: (1hp) = (63,025 in-lb-rpm)]

Torque load = (63,025 in-lb-rpm / hp)(gearbox input hp)(gearbox efficiency) / (motor rpm / (gearbox ratio)(pulley ratio))  
= (63,025)(1)(0.85) / (1725 / (15/1)(14.4/2.5)) = ~~2683 in-lb~~ [insufficient torque at load]

This torque value is less than the 2700 in-lb required by the load.

So, select and check the next larger nominal motor size, which is 1-1/2 hp.

Since the 206 frame size 15 ratio gearboxes do not meet the 1-1/2 hp thermal rating, choose the WG-237-015-x gearbox.

Select **1-1/2 hp motor** and **WG-237-015-x gearbox**, and check for adequate torque:

WG-237-015-x gearbox efficiency = 84%

maximum thermal input power = 1.55 hp

maximum mechanical input power @ 1.25 SF = 2.64 hp / 1.25 = 2.11 hp

maximum allowable motor power = 1.55 hp; select nominal 1-1/2 hp motor

gearbox ratio is still 15:1, and OHL rating is increased to 900 lb, so the previous pulley calculations [step 7] remain sufficient

[smaller pulleys can be calculated and selected for this gearbox, if desired]

Tload = (63,025 in-lb-rpm/hp) (1.5hp) (84%) / (1725 rpm / (15/1)(14.4/2.5)) = 3977 in-lb > 2700 in-lb; sufficient torque at load

**Final gearbox and motor selection: 1-1/2 hp motor WG-237-015-x gearbox**